Product data sheet
Characteristics

TMC2PACK01
cartridge M221 - packaging 2 analog inputs - I/O extension



Main

Range of product	Modicon M221
Product or component type	Analogue input cartridge
Product specific application	Packaging
Product compatibility	Modicon M221C
Analogue input number	2

Complementary

Analogue input type	Voltage, input range: 0...10 V Current, input range: 0...20 mA Current, input range: 4...20 mA
Analogue input resolution	12 bits
LSB value	3.91 µA (current), input range: 4...20 mA 4.88 µA (current), input range: 0...20 mA 2.44 mV (voltage), input range: 0...10 V
Conversion time	20 ms
Sampling duration	10 ms
Absolute accuracy error	+/- 1 % of full scale +/- 0.1 % of full scale at 25 °C
Temperature drift	+/- 0.02 %FS/°C
Repeat accuracy	+/- 0.5 %FS
Non-linearity	+/- 0.01 %FS
Cross talk	<= 1 LSB
Type of cable	Twisted shielded pairs cable
Electrical connection	2 screw terminal blocks (pitch 3.81 mm) 1.5 mm² 3 for inputs
Cable length	<= 30 m twisted shielded pairs cable (input)
Insulation	Non-insulated between analogue input and internal logic
Height	41 mm
Depth	15 mm
Width	35 mm
Product weight	0.015 kg
Permissible continuous overload	40 mA (current) 13 V (voltage)
Input impedance	>= 1 MOhm voltage <= 250 Ohm current

Environment

Immunity to microbreaks	10 ms

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1415 - Schneider Electric declaration of conformity
REACh	Reference contains SVHC above the threshold - go to CaP for more details
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Available Download End Of Life Manual