





Type Eyebolts	Type Assembly kit section/section	Type Assembly kit section/ IP55 section	Type DIN A4 circuit diagram pocket	Type Lock mechanism[1] roller lever with pushbutton	Type Adapter kit for profile half cylinder installation in XALP
Article no. 1 set (= 4 off)	Article no. 1 set (= 8 off)	Article no. 1 set (= 8 off)	Article no. 1 off each	Article no. 1 off each	Article no. 1 off each
XAT 283855	**XAC** 283483	**XAC 55** 284793	**XAB4** 283482	**XALP** 283821	**XALA** 283819

Notes [1] Lock mechanism with 3 mm double-ward key is included as standard in doors.


Type Profile half cylinder E012 incl. key	Type Edge protection for cable entries	Type 1 set of cover strips 45 mm standard front dimension for mounting plates, 12 SU	Type Hinge[2] for door opening angle 180°, right	Type Hinge[2] for door opening angle 180°, left	Type Specials colours to RAL
Article no. 1 off each	Article no. 1 set (2 m)	Article no. 10 off each	Article no. 2 off each	Article no. 2 off each	Article no. per order
XALE012 283820	**XAK** 283818	**XAS12** 284708	**XAH180** 284713	**XAH180L** 284792	**XARAL** 285005

Notes [2] For section height doors 3 hinges are required; the hinge cannot be used for cover plate.

Cross-section mm²	Length mm	Type Grounding cable Article no. per 20 pieces
4	180	**XAE4-18** 293897
4	420	**XAE4-42** 293898
10	180	**XAE10-18** 293896
10	420	**XAE-10** 284712

Supports for cable connection systems for circuit-breakers 800 – 4000 A

Support selection according to assembly manual BA4810-015



	I_e up to	Poles	Section width	Type Support cable connection system[1] Article no.
	A		mm	1 set each (per busbar)
Circuit-breakers				
IZM..2-..	3200	3	600	**XCSIY308** 283882
		4	800	**XCSIY412** 283884
IZM..3-..	4000	3	800	**XCSIY308** 283882
		4	1200	**XCSIY412** 283884

Notes [1] For connection bar 3 x 60 mm x 10 mm