

Restarting device-set, 220-240VAC, 6HP

Part no. Z-FW-LP/MO
Article no. 290171
Catalog No. Z-FW-LP/MO

Powering Business Worldwide

Delivery programme

Basic function			Accessories for miniature circuit breaker Accessories for residual current circuit breakers
Basic function accessories			Restarting device
Application			Switchgear for industrial and commercial applications
Product range			Accessory
Side mounting			for fitting on right to: CLS6, PFIM, PFHM-4p, dRCM, Z-A40, PFR, Z-MS

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I_n	A	0
Heat dissipation per pole, current-dependent	P_{vid}	W	0
Equipment heat dissipation, current-dependent	P_{vid}	W	0
Static heat dissipation, non-current-dependent	P_{vs}	W	3.5
Heat dissipation capacity	P_{diss}	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	40
			0

Technical data ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary contact unit for distribution board (EC001286)

Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss8.1-27-14-35-02 [AKE327010])

Device fitting			Universal
Additional equipment			Monitoring unit with automatic reclosing
Attached at delivery			No
Assembly width (TE)			6
Number of normally open contacts			0
Number of normally closed contacts			0
Number of change-over contacts			0
Number of fault-signal switches			0
Rated switch current		A	0
Nominal rated voltage		V	230
Control voltage type			AC
With autotest for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			0
Suitable for max. current main contact unit		A	0

© 11/2015 by Eaton Industries GmbH