Product data sheet
Characteristics

VW3S8201R15
cable for pulse/direction signal - 5 V - shielded - 1.5 m



Main

Accessory / separate part designation	Cable for pulse/direction signal
Accessory / separate part type	Connecting cable
Accessory / separate part category	Connection accessories
Accessory / separate part destination	Between stepper drive SD326 and external impulsion generator
Range compatibility	Lexium SD3
Type of cable	Shielded
Cable length	1.5 m

Complementary

Product compatibility	SD326
[Uc] control circuit voltage	5 V
Electrical connection	Cable end open for external impulsion generator 1 connector 24-pole Molex for SD326

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0932 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.