
Saves Your Energy

KARTA PRODUKTU
14.12.2015

NAD2.W

Nazwa:	**Distribution Block**
	White
Typ:	NAD2.W
GTIN:	6418677116117
Opis:	Distribution block with one in (for a socket) and three out (for plugs). The couplers to be connected to the distribution block are specified in the coupling illustration. If needed, the distribution block can be mounted to a base with two screws, max. ø 3,5 mm, distance between mounting holes 28 mm.
Opakowanie:	10/50/6250
Jednostka:	szt.





Specyfikacje techniczne

UL Wire range	14 AWG
Napięcie znamionowe	250 V
Stopień ochrony	IP20
Prąd znamionowy	20 A
ETIM	Compact distributor for plug-in building installation
Wymiary l x w x h	47x37x43
Max. operating temperature	+70 °C
Min. installation temperature	+5 °C
Min. operating temperature	-30 ºC (without mechanical stress)
Liczba biegunów	2
Materiał	Poliamid 66
Kolor	Biały
L	250 mm
UL Rated voltage	250 V
UL Rated current	16 A

Ensto Pol Sp. z o.o.
ul. Starogardzka 17 A
83-010 Straszyn, Poland
tel. +48 58 692 40 00
fax +48 58 692 40 20
www.ensto.pl

This product card has been printed from Ensto´s web-pages. Please, observe our legal notice on the front page of www.ensto.com.
© Ensto 2015