SM2.11

Nazwa:	**Zacisk odgałęźny**
	Al 16-95 mm² i Cu2.5-25 mm²
Typ:	SM2.11
GTIN:	6418677403903
Opis:	Zacisk SM 2.11 stosowany jest do wykonania połączenia nie obciążonego naprężeniem mechanicznym, przewodu aluminiowego z miedzianym . Zacisk jest oczyszczony i zabezpieczony pastą stykową. Zaciskany jest jedną śrubą M8.
Opakowanie:	100/6300
Jednostka:	szt.







Specyfikacje techniczne

Napięcie probiercze z osłoną	4 kV / 50 Hz / 1 min
ETIM	Branch terminal
Moment dokręcenia	20 Nm
Masa	0.08 kg
Żyła główna	Al 16-95
Przewód rozgałęźny	Cu 2.5-25
Średnica żyły	4.6-10 / 2.3-6.5
Bolt	M8
Osłona z tworzywa sztucznego	SP15
ETIM	
Nominal cross section main conductor, SE	16 … 95 mm²
Nominal cross section main conductor, SM	16 … 95 mm²
Nominal cross section branch conductor, SE/RE	2.5 … 25 mm²
Nominal cross section branch conductor, SM/RM	2.5 … 25 mm²
Material main conductor	Aluminium/copper
Material branch conductor	Aluminium/copper
Clamping channel opening main conductor	Both sides open
Clamping channel opening branch conductor	Both sides open

Ensto Pol Sp. z o.o.
ul. Starogardzka 17 A
83-010 Straszyn, Poland
tel. +48 58 692 40 00
fax +48 58 692 40 20
www.ensto.pl

This product card has been printed from Ensto´s web-pages. Please, observe our legal notice on the front page of www.ensto.com.
© Ensto 2015

SM2.11

Surface protection	Tinned
Type of connection	Screwed connection

Ensto Pol Sp. z o.o.
ul. Starogardzka 17 A
83-010 Straszyn, Poland
tel. +48 58 692 40 00
fax +48 58 692 40 20
www.ensto.pl

This product card has been printed from Ensto´s web-pages. Please, observe our legal notice on the front page of www.ensto.com.
© Ensto 2015