SL4.25

Nazwa:	**Zacisk odgałęźny**
	Al 16-120 mm² / Al 16-120 mm²
Typ:	SL4.25
GTIN:	6418677403750
Opis:	Zacisk SL 4.25 jest oczyszczony i zabezpieczony pastą stykową, wyposażony jest w sprężyny. Do wykonania połączenia przewodów aluminiowych nie obciążonego naprężeniem mechanicznym. Zaciskany jest dwoma śrubami M8.
Opakowanie:	50/3500
Jednostka:	szt.





Specyfikacje techniczne

Napięcie probiercze z osłoną	4 kV / 50 Hz / 1 min
ETIM	Branch terminal
Moment dokręcenia	20 Nm
Masa	0.13 kg
Żyła główna	Al 16-120
Przewód rozgałęźny	Al 16-120
Średnica żyły	4.6-13.5
Bolt	2xM8
Osłona z tworzywa sztucznego	SP15
ETIM	
Nominal cross section main conductor, SE	16 … 120 mm²
Nominal cross section main conductor, SM	16 … 120 mm²
Nominal cross section branch conductor, SE/RE	16 … 120 mm²
Nominal cross section branch conductor, SM/RM	16 … 120 mm²
Material main conductor	Aluminium
Material branch conductor	Aluminium
Clamping channel opening main conductor	Both sides open
Clamping channel opening branch conductor	Both sides open

Ensto Pol Sp. z o.o.
ul. Starogardzka 17 A
83-010 Straszyn, Poland
tel. +48 58 692 40 00
fax +48 58 692 40 20
www.ensto.pl

This product card has been printed from Ensto´s web-pages. Please, observe our legal notice on the front page of www.ensto.com.
© Ensto 2015

SL4.25

Surface protection	Bare
Type of connection	Screwed connection

Ensto Pol Sp. z o.o.
ul. Starogardzka 17 A
83-010 Straszyn, Poland
tel. +48 58 692 40 00
fax +48 58 692 40 20
www.ensto.pl

This product card has been printed from Ensto´s web-pages. Please, observe our legal notice on the front page of www.ensto.com.
© Ensto 2015