
Product data sheet
Characteristics

16315
cartridge C1 25-350 for surge arrester PRD1



Main

Range of product	PRD1
Product or component type	Cartridge
Device short name	C1 25-350
Surge arrester type	Electrical distribution network
Earthing system	TN TT

Complementary

Surge arrester class type	Type 1
Surge arrester technology	Spark gap
[Ue] rated operational voltage	230 V AC 50 Hz
Nominal discharge current	25 kA
[Iimp] impulse current	25 kA 25 kA 12.5 A.s
[Uc] maximum continuous operating voltage	350 V
[Up] voltage protection level	1.5 kV type 1
[If] follow current	25 kA
Local signalling	Flag color: white/red
Mounting mode	Plug-in
Mounting support	Into SPD module
9 mm pitches	2.5
Height	50 mm
Width	23 mm
Depth	57 mm
Colour	Anthracite grey (RAL 7016)
Material	PBT (polybutylene terephthalate)
Response time	< 100 ns

Environment

Standards	EN 61643-11 IEC 61643-1
Product certifications	KEMA-KEUR
IP degree of protection	Front face : IP20
Relative humidity	5...90 %
Operating altitude	0...2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...80 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0902 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.