TOPJOB®S

Plug-In Component Module for Terminal Jumper Location, Series 2002

Diode Module; Diode 1 N 4007 **U_N 250 V; U_{RM} 1000 V; 1 A max.** **Width 10.4 mm / 0,409 in**		**LED-Module:** **$I_N \leq 5{,}6$ mA; $I_F \leq 25$ mA** **Width 10.4 mm / 0.409 in**







Item No.	Pack Unit		Item No.	Pack Unit
Empty Module, 10.4 mm wide,			**LED Module,** 10.4 mm wide, with red LED	
			AC/DC 12 - 30 V	
2002-880	50		**2002-880/1000-541**	50
Diode Module, 10.4 mm wide,			**LED Module,** 10.4 mm wide, with red LED	
 Diode 1N 4007			AC/DC 30 - 65 V	
2002-880/1000-411	50		**2002-880/1000-542**	50
			LED Module, 10.4 mm wide, with red LED	
			AC/DC 110 - 250 V	
			2002-880/1000-836	50

Terminal Blocks and Accessories

Appropriate marker systems: Terminal block WMB/marker strips (see pages 80-85)

2-Conductor Terminal Block, ❶			**2-Conductor Terminal Block,** ❶	
 0.25 – 2.5 (4) mm²/AWG 22 – 12			 0.08 – 2.5 (4) mm²/AWG 28 – 12	
width 5.2 mm /0.205 in			width 5.2 mm /0.205 in	
gray **2002-1201**	100		gray **2002-1201**	100
End and Intermediate Plate, 0.8 mm thick			**End and Intermediate Plate,** 0.8 mm thick	
 orange **2002-1292**	100 (4 x 25)		 orange **2002-1292**	100 (4 x 25)
gray **2002-1291**	100 (4 x 25)		gray **2002-1291**	100 (4 x 25)
3-Conductor Terminal Block, ❷			**3-Conductor Terminal Block,** ❷	
 0.25 – 2,5 (4) mm²/AWG 22 – 12			 0.08 – 2.5 (4) mm²/AWG 28 – 12	
width 5.2 mm /0.205 in			width 5.2 mm /0.205 in	
gray **2002-1301**	100		gray **2002-1301**	100
End and Intermediate Plate, 0.8 mm thick			**End and Intermediate Plate,** 0.8 mm thick	
 orange **2002-1392**	100 (4 x 25)		 orange **2002-1392**	100 (4 x 25)
gray **2002-1391**	100 (4 x 25)		gray **2002-1391**	100 (4 x 25)
4-Conductor Terminal Block, ❸			**4-Conductor Terminal Block,** ❸	
 0.25 – 2.5 (4) mm²/AWG 22 – 12			 0.08 – 2.5 (4) mm²/AWG 28 – 12	
width 5.2 mm /0.205 in			width 5.2 mm /0.205 in	
gray **2002-1401**	100		gray **2002-1401**	100
End and Intermediate, 0.8 mm thick			**End and Intermediate Plate,** 0.8 mm thick	
 orange **2002-1492**	100 (4 x 25)		 orange **2002-1492**	100 (4 x 25)
gray **2002-1491**	100 (4 x 25)		gray **2002-1491**	100 (4 x 25)

❶ 48.5 mm / 1.91 in (2-Conductor)
❷ 59.5 mm / 2.34 in (3-Conductor)
❸ 70.0 mm / 2.76 in (4-Conductor)