KMC

Stycznik
KMC Contactor







KMC







PL

Stycznik: służy do automatycznego włączania odbiorników energii elektrycznej
Kategorie użytkowania: AC7a, AC7b
Zgodność z normą: IEC/EN 60947-4-1, IEC/EN 61095
Moc znamionowa: do 40kW
Napięcie znamionowe cewki: 230V AC 50/60Hz
Temperatura pracy: -25°C do +40°C
Pojemność zacisków:
- linka 1,5mm² do 10mm² KMC-20/25
- drut 2,5mm² do 25mm² KMC-63
Stopień ochrony: IP20

GB

A contactor: used for automatically switching on electric energy receivers
Utilization categories: AC7a, AC7b
Compliance with: IEC/EN 60947-4-1, IEC/EN 61095
Rated power: up to 40kW
Rated voltage of coil: 230V AC 50/60Hz
Operating temperature: -25°C to +40°C
Capacity of terminals:
- cord 1,5mm² to 10mm² KMC-20/25
- wire 2,5mm² to 25mm² KMC-63
Degree of protection: IP20

STYK CONTACT		PRĄD ZNAMIONOWY IN(A) RATED CURRENT IN(A)		MOC ZNAMIONOWA [kW] RATED POWER [kW]					
ZWIERNY (NO) NORMALLY OPEN (NO)	ROZWIERNY (NC) NORMALLY CLOSED (NC)	AC-7A/AC-1	AC-7B/AC-1	AC-7A/230V	AC-7B/230V	NAPIĘCIE STERUJĄCE CONTROL VOLTAGE	SYMBOL SYMBOL	INDEKS INDEX	PAKOWANIE PACKAGING
2	0	20	7	4	1,2	230V AC	KMC-20-20	23240	-/12/120
1	1	20	7	4	1,2	230V AC	KMC-20-11	23244	-/12/120
0	2	20	7	4	1,2	230V AC	KMC-20-02	23243 "I"	-/12/120
				AC-7A/400V	AC-7B/400V				
4	0	20	7	13	3,5	230V AC	KMC-20-40	23241	-/6/60
0	4	25	8,5	15	4	230V AC	KMC-25-04	23245	-/6/60
2	2	25	8,5	15	4	230V AC	KMC-25-22	23246	-/6/60
3	1	25	8,5	15	4	230V AC	KMC-25-31	23247	-/6/60
4	0	63	25	40	13	230V AC	KMC-63-40	23242	-/4/40
0	4	63	25	40	13	230V AC	KMC-63-04	23248 "I"	-/4/40
2	2	63	25	40	13	230V AC	KMC-63-22	23249 "I"	-/4/40
3	1	63	25	40	13	230V AC	KMC-63-31	23250 "I"	-/4/40