ASSMANN BUSINESS SHOP
ORIGINAL ASSMANN QUALITY

DIGITUS CAT 3 ISDN patch panel, unshielded

DN-91350-1 4016032269021



50-port RJ45, 8P4C, LSA, 1U, Rack Mount Color grey RAL 7035

Best performance and link quality for your network

- Suitable for 483mm (19") Rack Mount
- Material housing: SECC, 1,5mm Electrogalvanized, Cold-rolled Steel accc. EN1.4301, UNS S30400, AISI 304 and LMSAD110
- Unshielded RJ45 jacks
- Material contacts: Phosphor bronze
- Contacts coating: Nickel, gold plated 0,3µ
- Cable installation via LSA strips, color coded according to EIA/TIA 568 A & B
- Material IDC Terminal: Phosphor Bronze with 50µ Tin plated over 60µ Nickel plated
- Material PCB: FR4, UL 94V-0, multilayer 1,45mm thickness
- Insertion force: ≤ 30N
- Mating cycles: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- Operating temperature: -20°C ... +70°C
- Current carrying capacity: 1A at 50°C
- Isolation resistance > 500MOhm
- Category: CAT 3
- Ports: 50
- Color: light grey, RAL 7035
- Units: 1





DIGITUS CAT 3 ISDN patch panel, unshielded

DN-91350-1 4016032269021

→ Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	12,00	53,50	32,00	28,00	47936,00
Packaging Unit Inside	1	1,20	15,00	52,00	5,50	4290,00
Packaging Unit Single	1	1,20	15,00	52,00	5,50	4290,00
Net single without Packaging	1	0,00	4,50	48,50	13,50	2946,38

→ Packaging type



Country of origin: China