18 Series
PIR movement detectors



18.41.8.230.0300

Surface/recessed mounting corridor detector
30 m x 4 m sensing area
1 NO (SPST) 10 A volt-free output, 110-230 V AC operation
Adjustable ambient light threshold 1-500 lx and light ON time 12 s - 35 min
Adjustable range/sensitivity
Quick connect push-in terminals
Incandescent lamp load 1000 W, compensated fluorescent load 350 W



18.51.8.230.0300

Surface/recessed mounting movement/presence detector
Dual sensing areas: movement 8 m x 8 m; presence 4 m x 4 m
1 NO (SPST) 10 A volt-free output, 110-230 V AC operation
Adjustable ambient light threshold 1-500 lx and light ON time 12 s - 35 min
Adjustable range/sensitivity
Quick connect push-in terminals
Incandescent lamp load 1000 W, compensated fluorescent load 350 W



18.01.8.230.0000

Internal universal wall mounting detector
1 NO (SPST) 10 A switched live output, 120-230 V AC operation
Adjustable ambient light threshold 5-350 lx and light ON time 10 s - 12 min
Incandescent lamp load 1000 W, compensated fluorescent load 350 W



18.11.8.230.0000

External (IP54) universal wall mounting detector
1 NO (SPST) 10 A switched live output, 120-230 V AC operation
Adjustable ambient light threshold 5-350 lx and light ON time 10 s - 12 min
Incandescent lamp load 1000 W, compensated fluorescent load 350 W



18.21.8.230.0000

Ceiling surface mounting detector
1 NO (SPST) 10 A switched live output, 120-230 V AC operation
Adjustable ambient light threshold 5-350 lx and light ON time 10 s - 12 min
Incandescent lamp load 1000 W, compensated fluorescent load 350 W



18.31.8.230.0000

Ceiling recessed mounting detector
1 NO (SPST) 10 A switched live output, 120-230 V AC operation
Adjustable ambient light threshold 5-350 lx and light ON time 10 s - 12 min
Incandescent lamp load 1000 W, compensated fluorescent load 350 W



18.21.8.230.0031

High ceiling (6 m) surface mounting detector
1 NO (SPST) 10 A switched live output, 120-230 V AC operation
Adjustable ambient light threshold 5-350 lx and light ON time 30 s - 35 min
Incandescent lamp load 1000 W, compensated fluorescent load 350 W



18.31.8.230.0031

High ceiling (6 m) recessed mounting detector
1 NO (SPST) 10 A switched live output, 120-230 V AC operation
Adjustable ambient light threshold 5-350 lx and light ON time 30 s - 35 min
Incandescent lamp load 1000 W, compensated fluorescent load 350 W



18.21.0.024.0300
18.21.8.230.0300

Ceiling surface mounting detector
1 NO (SPST) 10 A volt-free output, 120-230 V AC or 24 V AC/DC operation
Adjustable ambient light threshold 5-350 lx and light ON time 10 s - 12 min
Incandescent lamp load 1000 W, compensated fluorescent load 350 W



18.31.0.024.0300
18.31.8.230.0300

Ceiling recessed mounting detector
1 NO (SPST) 10 A volt-free output, 120-230 V AC or 24 V AC/DC operation
Adjustable ambient light threshold 5-350 lx and light ON time 10 s - 12 min
Incandescent lamp load 1000 W, compensated fluorescent load 350 W

finder®

findernet.com

Opal Way - Stone Business Park
STONE, STAFFORDSHIRE,
ST15 0SS - UK

Tel. +44 (0)1785 818100
Fax +44 (0)1785 815500
Email finder.uk@findernet.com

August 2013