SIEMENS

Data sheet 3SE2932-0AB20

FOOT-OPERATED PUSHBUTTON TWO PEDALS, CABLE ENTRY M20X1,5 WITHOUT IP65, 1N0+1NC



Figure similar

Product designation	momentary-contact foot switch
General technical data:	
Protection class IP	IP65
Equipment marking	
• acc. to DIN EN 61346-2	S
• acc. to DIN EN 81346-2	S
Number of switching steps	1
Number of the actuation pedals	2
Enclosure:	
Material of the enclosure	metal
Color	
• of the enclosure	black
• of top part of the enclosure	grey
Safety related data:	
B10 value with high demand rate acc. to SN 31920	1 000 000
Proportion of dangerous failures	
• with low demand rate acc. to SN 31920	50 %
• with high demand rate acc. to SN 31920	50 %

Changes preserved
© Copyright Siemens AG

T1 value for proof test interval or service life acc. to IEC 61508	20 y

Mechanical data:

Cable entry type	M25 x 1.5

Ambient conditions:

Ambient temperature	
• during operation	-25 ... +80 °C

Installation/ mounting/ dimensions:

Mounting type	screw fixing
Height	221 mm
Width	193 mm
Depth	63 mm

Certificates/approvals

General Product Approval			Declaration of Conformity	Shipping Approval	
CCC	CSA	EAC	EG-Konf.	ABS	LRS

Shipping Approval		other	
PRS	RINA	sonstig	Bestätigungen

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SE29320AB20

Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SE29320AB20

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3SE29320AB20

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SE29320AB20&lang=en

Changes preserved
© Copyright Siemens AG



last modified: 16.03.2016

Changes preserved
© Copyright Siemens AG