

Wskaźnik zużycia energii / Energy consumption meter



EDM 1P LCD R





Constant 2000imp/kWh
Class 1.0 (ti=80ms) so
Ui max = 27V / Ii max=27mA

- obudowa: tworzywo sztuczne
- casing: plastic

Kanlux EDM 1P LCD R	Kanlux 19340

220-240V~ | 50/60Hz | Ib 5A | Imax 30A | Imin 0,02A | 0,5Wh /imp | max ≤ 6VA | IP 20 | -25 ÷ 70 [°C] | DIN 35mm | 1P | 1P | 1/-/80 | 90 [g] | Class I | CE


przeznaczony jest do pomiarów zużycia energii elektrycznej w instalacjach jednofazowych, może być używany jako podlicznik głównego licznika budynku, piętra lub mieszkania / dokładność wskazań miernika do 0,1 kWh / zakres pomiarowy miernika do 999999,9 kWh / istnieje możliwość plombowania / wyświetlacz: LCD 6+1
intended for measuring electric power consumption in single-phase installations; can be used as a sub-meter of the main meter in the building, on one floor, or in one apartment / meter measurement precision of up to 0,1 kWh / measurement range of up to 999999,9 kWh / can be sealed / display: LCD 6+1

Gniazdo / Electric socket

KMFS



KMFS-16A



- obudowa: tworzywo sztuczne
- casing: plastic

Kanlux KMFS-16A	Kanlux 19490

250V~ | 50/60Hz | In 16A | IP 20 | -5 ÷ 40 [°C] | DIN 35mm | 1 ÷ 25 [mm²] | 3P | 1/-/100 | 90 [g] | CE

wyposażone w styk ochronny / equipped with protective conductor contact