SIEMENS

Data sheet 3TH43 91-0BB4

EN 50 011 EN 50 011 9NO+1NC, SCREW TERMINALS DC OPERATION DC SOLENOID SYSTEM DC 24V



Figure similar

General technical data:	
Size of contactor	0
Ambient temperature during operation	-25 ... +55 °C
Protection class IP on the front	IP20
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Equipment marking acc. to DIN EN 61346-2	K
Equipment marking acc. to DIN EN 81346-2	K

Control circuit/ Control:	
Type of voltage of the control supply voltage	DC
Control supply voltage	
• at DC	
— rated value	24 V

Auxiliary circuit:	
Operating current at AC-15	
• at 230 V rated value	10 A
• at 400 V rated value	6 A

Changes preserved
© Copyright Siemens AG

Identification number and letter for switching elements	91 E
Number of NC contacts for auxiliary contacts	1
• lagging switching	0
• delayed switching	0
• make-before-break switching	0
Number of NO contacts for auxiliary contacts	9
• delayed switching	0
• leading contact	0
• make-before-break switching	0
Number of CO contacts for auxiliary contacts	0

Connections/ Terminals:

Type of electrical connection for auxiliary and control current circuit	screw-type terminals

Mechanical data:

Mounting type	screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
Width	55 mm
Height	78 mm
Depth	135 mm

Certificates/approvals

General Product Approval				Declaration of Conformity	Test Certificates
CCC	CSA	UL	EAC	EG-Konf.	Typprüfbescheinigung/Werkszeugnis

Test Certificates		Shipping Approval			
spezielle Prüfbescheinigungen	sonstig	DNV	GL	LRS	RMRS

other	
Umweltbestätigung	sonstig

Safety related data:

Changes preserved
© Copyright Siemens AG

Protection against electrical shock	finger-safe
B10 value with high demand rate acc. to SN 31920	1 000 000
• Note	With 0.3 x Ie
T1 value for proof test interval or service life acc. to IEC 61508	20 y

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TH43910BB4

Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TH43910BB4

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3TH43910BB4

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TH43910BB4&lang=en



\W9 4444;
\W9.25; 3TH4391-0BB4_ALL

last modified: 23.11.2015

Changes preserved
© Copyright Siemens AG