SIEMENS

Data sheet 5SY5206-7

CIRCUIT BREAKER CURR. SENS DC 440V AC 400V 10KA, 2-POLE, C, 6A



Model		
product brand name		SENTRON
Product designation		5SY miniature circuit breaker
Design of the product		5SY miniature circuit breakers
General technical data		
Number of poles		2
Number of poles / Note		2P
Tripping characteristic class		C
circuit-breaker / Design		5SY5
Mechanical service life (switching cycles) / typical		20 000
Overvoltage category		3
Voltage		
Type of voltage		AC/DC
Insulation voltage		
• at DC / rated value	V	250
• with multi-phase operation / at AC / rated value	V	440
Supply voltage		
Supply voltage / at AC / rated value	V	400

Changes preserved
© Copyright Siemens AG

Protection class		
Protection class IP		IP20, with connected conductors
Energy limiting class		3
Switching capacity		
Switching capacity current		
• at DC / acc. to IEC 60947-2 / rated value	kA	15
• acc. to EN 60898 / rated value	kA	10
Dissipation		
Power loss [W]		
• for rated value of the current / at AC / in hot operating state / per pole	W	1.6
• maximum	W	3.2
Electricity		
Current / at AC / rated value	A	6
Product details		
Product feature / Touch protection		Yes
Product component		
• combined terminal top		Yes
• combined terminal bottom		Yes
Product feature		
• Properties for main switches in accordance with EN 60204-1		Yes
• halogen-free		Yes
• sealable		Yes
• silicon-free		Yes
Product extension / can be installed / supplementary devices		Yes
Product function		
Product function / neutral conductor switching		No
Short circuit		
Breaking capacity short-circuit current (Icn)		
• at DC / acc. to EN 60898-2	kA	10
Number		
Number of test cycles / for environmental testing / acc. to IEC 60068-2-30		6
Connections		
Connectable conductor cross-section / stranded		
• minimum	mm²	0.75
• maximum	mm²	35

Changes preserved
© Copyright Siemens AG

Connectable conductor cross-section		
• solid		
— minimum	mm²	0.75
— maximum	mm²	35
• finely stranded / with core end processing		
— minimum	mm²	0.75
— maximum	mm²	25
AWG number / as coded connectable conductor cross section		
• minimum		14
• maximum		4
Tightening torque [lbf·in] / with screw-type terminals		
• minimum	lbf·in	22
• maximum	lbf·in	26
Tightening torque / with screw-type terminals		
• minimum	N·m	2.5
• maximum	N·m	3

Mechanical Design		
Height	mm	90
Width	mm	36
Depth	mm	76
Mounting position		any
Installation depth	mm	70
Number of width units		2
Mounting type		Quick assembly system
Net weight	g	300

Environmental conditions		
Influence of the surrounding temperature		Max. 95% humidity
Shock resistance / acc. to IEC 60068-2-27		150m/s² at 11ms half-sine
Vibration resistance / acc. to IEC 60068-2-6		50m/s² at 25 to 150Hz and 60m/s² at 35Hz (4sec)
Ambient temperature		
• minimum	°C	-25
• maximum	°C	55
• during storage / minimum	°C	-40
• during storage / maximum	°C	75

Certificates		
Equipment marking / acc. to DIN EN 61346-2		F

Changes preserved
© Copyright Siemens AG

General Product Approval			Declaration of Conformity	Test Certificates
CCC	VDE		EG-Konf.	sonstig

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)
https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5SY52067

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
http://support.automation.siemens.com/WW/view/en/5SY52067/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SY52067

CAx-Online-Generator
http://www.siemens.com/cax

Tender specifications
http://ausschreibungstexte.siemens.com/tiplv





Changes preserved
© Copyright Siemens AG

last modified: 12.04.2016

Changes preserved
© Copyright Siemens AG