
Saves Your Energy

PRODUCT CARD
20.6.2016

SEW20.7

Name:	**Connector**
	CC Al 50-157 / Bare Al 35-157 mm²
Type:	SEW20.7
GTIN:	6438100310493
Description:	The connector SEW20.7 can be used for medium voltage covered conductor to bare conductor connections. The connector is watertight by silicone greased teeth.
Package:	25/1750
Unit:	PCS





Technical specification

Ratings	
ETIM class	EC001062
Mechanical	
Tightening torque	40 Nm
Dimensions	
Weight	0.27 kg
Main conductor mm²	Bare 35-157 mm²
Branch conductor mm²	CC 50-157 mm²
Features	
Bolt	2xM10
Certificates	
Standards	EN 50397-2:2009
ETIM	
Material main conductor	Aluminium
Material branch conductor	Aluminium
Clamping channel opening main conductor	Both sides open
Clamping channel opening branch conductor	Both sides open
Surface protection	Bare
Type of connection	Insulation piercing connector IPC

Ensto Finland Oy
Ensio Miettisen katu 2
P.O.Box 77
06101 Porvoo, Finland
Tel. +358 204 76 21
Fax +358 204 76 2770
www.ensto.com

This product card has been printed from Ensto´s web-pages. Please, observe our legal notice on the front page of www.ensto.com.
© Ensto 2016