Saves Your Energy

PRODUCT CARD

20.06.2016

HOTU3.2401

Głowica termokurczliwa

Typ	HOTU3.2401
GTIN	6418677450730
Nazwa	Głowica termokurczliwa napowietrzna; 12/20 (24)kV; Cu 10-16mm²; uniwer. 3 żył., bez końców.
Opis	Głowica napowietrzna stosowana do kabli uniwersalnych 3 żyłowych typu EXCEL i FXCEL o maksymalnym napięciu 24 kV. Zestaw zawiera komplet komponentów na trzy fazy, tj. taśmy, chusteczki, papier ścierny, elementy sterowania polem, trójpalczatkę i rury termokurczliwe odporne na wyładowania powierzchniowe oraz klosze. Zestaw nie zawiera końcówek kablowych.



Specyfikacje techniczne

Dimensions

Masa: 1.17 kg
Przekrój żyły 24 kV: Al/Cu 10-16
Droga upływu: 650 mm
Długość głowicy: 450 ... 1100 mm
Średnica klosza: 90 mm

Features

Liczba kloszy na fazę: 3

Ratings

ETIM: EC000910

UN Search filters

Voltage class: 12/20 | 12,7/22 (24) kV
Accessory type: Termination, outdoor
Insulation material: Plastic
Screen/Shield material: Cu-wire
Conductor size mm²: 10, 16
No. of cores: 3
Conductor size Al 24 kV mm²: 10, 16
Conductor size Cu 24 kV mm²: 10

ETIM

ETIM

Model: Heat-shrink
Voltage row: 12/20 kV
Nominal cross section: 10 ... 16 mm²
Number of conductors: 3

Opakowanie

Opakowanie

Unit: PCS

Straszyn

ul. Starogardzka 17a
83-010 Straszyn
Polska

Email biuro@ensto.com
Tel. 58 692 40 00

www.ensto.com