Saves Your Energy

PRODUCT CARD
21.06.2016

ECO900

Sterownik do ochrony przeciwoblodzeniowej



Typ	ECO900
GTIN	6418677630866
Nazwa	Sterownik do ochrony przeciwoblodzeniowej Sterownik do ochrony przeciwoblodzeniowej terenów zewnętrznych, ramp i dachów
Opis	ECO900 thermostat requires always a sensor pair (Outdoor Areas frost protection: ECOA901 + ECOA902 or rainwater system frost protection: ECOA903 + ECOA904).
Producent	Ensto Finland Oy

Specyfikacje techniczne

Dimensions

Masa:	0.8 kg
Wymiary l x w x h:	105x90x60

Ratings

Napięcie znamionowe:	230 V
Stopień ochrony:	
Moc:	3600 W
ETIM:	EC001666

ETIM

ETIM

Degree of protection (IP):	IP20
Model:	Digital
Number of channels:	1
Operation mode switch:	1
Width in number of modular spacings:	6
Sensor type:	Other
Rated voltage:	230 V

Ensto Pol Sp. z o.o.
ul. Starogardzka 17A
83-010 Straszyn
Poland
email: biuro@ensto.com
phone: +801 360 066
www.ensto.com

Nominal rated frequency:	50 Hz
Text guidance in display:	1
Switching preselection:	1
Nominal switching current at 230 V, not potential free:	16 A
Assembly depth:	60 mm

Opakowanie

Opakowanie

Unit:	PCS
Size:	1
Weight (net):	0.66 kg

Pallet package

Unit:	PCS
Size:	180