Saves Your Energy

PRODUCT CARD

21.06.2016

SDI90.150

Kompozytowy izolator odciągowy.

Typ	SDI90.150
GTIN	6418677422669
Nazwa	Kompozytowy izolator odciągowy. 12...24 kV, 70 kN, okucia ucho owalne - ucho owalne
Opis	Izolator do słupów odporowych i końcowych linii 12-24 kV. Idealny do linii 24 kV w pierwszej strefie zabrudzeniowej (IEC60815).



Specyfikacje techniczne

Dimensions

Masa:	0.99 kg
Droga upływu:	391 mm

Electrical values

Najwyższe napięcie systemu:	24 kV
Napięcie wytrzymywane udarowe piorunowe na sucho:	≥ 126 kV
Napięcie wytrzymywane przemienne o częstotliwości sieciowej w deszczu:	≥ 57 kV

Features

End fittings:	eye / eye

Mechanical

SMFL:	70 kN
Obciążenie w badaniach wyrobu (RTL):	35 kN

Ratings

ETIM:

Specification

Use:	Insulator for terminal and intermediate poles of 24 kV lines.
Construction:	

Straszyn
ul. Starogardzka 17a
83-010 Straszyn
Polska
email: biuro@ensto.com
phone: 58 692 40 00
www.ensto.com

Construction:

Component	Material
Sheds	Reliable Grey Silicone rubber
Central rod	Corrosion Resistant Fiberglass
End-fittings	Hot-dip galvanised steel

Markings: SDI90.150

Standard: IEC 61109

Opakowanie

Opakowanie

Unit: PCS

Size: 3

Length: 525 mm

Width: 340 mm

Height: 110 mm

Weight (net): 2.985 kg

Weight (brt): 3.015 kg

Volume: 0.0196

Pallet package

Unit: PCS

Size: 114

Length: 1200 mm

Width: 800 mm

Height: 1020 mm

Weight (net): 113.43 kg

Weight (brt): 134 kg

Volume: 0.9792