Saves Your Energy

PRODUCT CARD

21.06.2016

SDI27.1

Układ ochrony przeciwłukowej



Typ	SDI27.1
GTIN	6418677419133
Nazwa	Układ ochrony przeciwłukowej
	Do izolatorów odciągowych linii PAS
Opis	Układ ochrony przeciwłukowej linii PAS SDI 27.1 montowany na izolatorach odciągowych serii SDI 90 na stanowiskach narożnych z uchwytem przelotowo-narożnym SO 181.6 a na stanowiskach odporowych (końcowych) z uchwytami SO 255 i SO 256 . Przerwa iskrowa 130-150 mm dla 24-36 kV. Test odporności na łuk: 2 x 10 kA, 1s; prąd zwarcia : I1s=11,5 kA, 1s; Idyn=29 kA

Specyfikacje techniczne

Dimensions

Masa: 0.83 kg

Electrical values

Napięcie znamionowe (Un): 12 ... 36 kV

Odstęp elektrod iskiernika: 95 ... 230 mm

Ratings

ETIM: EC000490

Specification

Use: SDI27.1 is used as an arcing protection device for SDI90 series insulators, with SO181.6, SO256 or SO255 clamps.

Construction: The kit SDI27.1 consists of following parts

Construction:

Component	Material
Al - parts	Corrosion resistant aluminium alloy,
Steel parts	Hot-dip galvanised steel

Straszyn

ul. Starogardzka 17a
83-010 Straszyn
Polska

email: biuro@ensto.com
phone: 58 692 40 00

www.ensto.com

Installation:	One end of the conductor will be installed on the clamp and another on the SDI10.2
Tools required:	Articulated spanner ST20
Markings:	SDI27.1

ETIM

ETIM

Type of accessory:	Ground spike
Material:	Steel
Surface protection:	Hot dip galvanized

Opakowanie

Opakowanie

Unit:	PCS
Size:	9
Length:	385 mm
Width:	260 mm
Height:	165 mm
Weight (net):	7.47 kg
Weight (brt):	7.72 kg
Volume:	0.0165

Pallet package

Unit:	PCS
Size:	486
Length:	1200 mm
Width:	800 mm
Height:	1140 mm
Weight (net):	403.38 kg
Weight (brt):	424 kg
Volume:	1.0944