QS 45X45 C - QUADRO socket module with protective contacts (schuko) and screens





MAT PC-ABS IP 20

- For 1.5-2.5 mm² Cu wires. The fixing of the conductor is performed by means of screws.
- Rated voltage 250 V AC, rated current 16 A.
- Installation by snap-on movement only.
- The sockets can be connected together; the max. number is limited by the tray or box.
- The use of the PIN system (with pin) and the SCHUKO system (with spring contacts) sockets should be according to the standards of each particular country.
- Also for KOPOBOX floor boxes and KOPOBOX MINI multi-purpose boxes.

item	conf.	for trunkings		pcs	EAN
QS 45X45 C	**HB**	PK 90X55 D, PK 120X55 D, PK 160X65 D, PK 210X70 D	white	10	8595568919502
	BB		red	10	8595568919519

QD 45X22.5 - modular sockets QUADRO - data

- Simple snap-on installation.
- Sockets can be connected with each other; maximum number of sockets is defined by the type of the sill channel or the type of KOPOBOX series box.

MAT PC-ABS IP 20

	item	conf.	dimension mm	for trunkings		pcs	EAN
	QD 45X22.5 – COVER	**HB**	45 x 22,5 x 17	PK 90X55 D, PK 120X55 D, PK 160X65 D, PK 210X70 D	white	20	8595568927231
	**QD 45X22.5 – RJ-12**	**HB**	45 x 22,5 x 36		white	10	8595568927262
	**QD 45X22.5 – RJ-45**	**HB**	45 x 22,5 x 36		white	10	8595568927279
	**QD 45X22.5 – HDMI**	**HB**	45 x 22,5 x 36		white	10	8595568927248
	**QD 45X22.5 – USB**	**HB**	45 x 22,5 x 36		white	10	8595568927255

MAT material
IP protection
color
package