Control and signalling units Ø 22

Harmony® XB4 metal

Multiple-headed pushbuttons, spring return

User assembly of other units, using:
body-contact assemblies: see page 36068-EN/2
combined sub-assemblies: see page 36068-EN/8
accessories: see page 36069-EN/2

569134



XB4 BL73415

569136



ZB4 BA7121

569138



ZB4 BL7341

569140



XB4 BW73731●5

569142



ZB4 BW7A1721

569150



ZB4 BW7A3741

Double-headed pushbuttons *(1)*

Screw clamp terminal connections (Schneider Electric anti-retightening system)

Shape of head	Description	Type of contact N/O	Type of contact N/C	Colour and marking of caps *(2)*	Reference	Weight kg
Complete units						
	2 pushes (1 flush black + 1 projecting red)	1	1	White “I” on green background White “0” on red background	**XB4 BL73415**	0.116
Heads only						
	2 flush black pushes			White background + black background, unmarked	**ZB4 BA7120**	0.056
				Black “I” on white background White “0” on black background	**ZB4 BA7121**	0.056
				Green background + red background, unmarked	**ZB4 BA7340**	0.056
				White “I” on green background White “0” on red background	**ZB4 BA7341**	0.056
				Without cap *(3)*	**ZB4 BA79**	0.056
	1 flush black push 1 projecting red push			Green background + red background, unmarked	**ZB4 BL7340**	0.056
				White “I” on green background White “0” on red background	**ZB4 BL7341**	0.056

Double-headed pushbuttons + 1 white central pilot light block *(1)*

Screw clamp terminal connections (Schneider Electric anti-retightening system)

Shape of head	Description	Type of contact N/O	Type of contact N/C	Colour and marking of caps *(2)*	Pilot light voltage V	Reference	Weight kg
Complete units							
Protected LED	**1 flush black push 1 projecting red push 1 white central pilot light block**	1	1	White “I” on green background White “0” on red background	24	**XB4 BW73731B5**	0.130
					120	**XB4 BW73731G5**	0.130
					240	**XB4 BW73731M5**	0.130
Heads only *(5)*							
Protected LED	**2 flush black pushes 1 clear central pilot light** *(4)*			White background + black background, unmarked		**ZB4 BW7A1720**	0.056
				Black “I” on white background White “0” on black background		**ZB4 BW7A1721**	0.056
				Green background + red background, unmarked		**ZB4 BW7A3740**	0.056
				White “I” on green background White “0” on red background		**ZB4 BW7A3741**	0.056
				Black “⬆” on white background White “⬇” on black background		**ZB4 BW7A1724**	0.056
				Black “+” on white background Black “–” on white background		**ZB4 BW7A1715**	0.056
				Without cap *(3)*		**ZB4 BW7A9**	0.056
Protected LED	**1 flush black push 1 projecting red push 1 clear central pilot light** *(4)*			Green background + red background, unmarked		**ZB4 BW7L3740**	0.056
				White “I” on green background White “0” on red background		**ZB4 BW7L3741**	0.056

Heads with black metal bezel

To order. add the suffix **7** to the references selected above. Example: **ZB4 BA7120** becomes **ZB4 BA71207**.

(1) *Recommended maximum number of contacts constituting the body (fixing collar + contact) associated with the head, see page 36072-EN/2.*
(2) These caps are fitted by Schneider Electric and cannot be removed (risk of damage).
(3) Caps to be ordered separately: see page opposite.
(4) Colour of centrally positioned pilot light determined by the colour of the LED incorporated in the body sub-assembly.
(5) Only for use with bodies comprising a light source with integral LED.

General : page 36022-EN/2
Characteristics : page 36001-EN/2
Dimensions : page 36020-EN/2

Control and signalling units Ø 22
Harmony® XB4 metal
Multiple-headed pushbuttons, spring return

User assembly of other units, using:
body-contact assemblies: see page 36068-EN/2
combined sub-assemblies: see page 36068-EN/8
accessories: see page 36069-EN/2

Triple-headed pushbuttons *(1) (2)*
Screw clamp terminal connections (Schneider Electric anti-retightening system)

Shape of head	Description	Type of contact N/O	Type of contact N/C	Type of contact N/O	Colour and marking of caps *(3)*	Reference	Weight kg
Complete units							
	**2 flush black pushes + 1 central projecting red push marked "Stop" in white**	1	1	1	White "I" on green background White "II" on green background	**XB4 BA731327**	0.128
					Black "➡" on white background White "⇦" on black background	**XB4 BA711237**	0.128
Heads only							
	**2 flush black pushes + 1 central projecting red push marked "Stop" in white**				White "I" on green background White "II" on green background	**ZB4 BA73132**	0.056
					White "⇦" on green background White "⇨" on green background	**ZB4 BA73133**	0.056
					White "⇧" on green background White "⇩" on green background	**ZB4 AA73134**	0.056
					White "+" on green background White "–" on green background	**ZB4 BA73135**	0.056
					Black "+" on white background Black "–" on white background	**ZB4 BA71115**	0.056
					Black "➡" on white background White "⇦" on black background	**ZB4 BA71123**	0.056
					Black "⬆" on white background White "⇩" on black background	**ZB4 BA71124**	0.056
					White "⇧" on black background White "⇩" on black background	**ZB4 BA72124**	0.056
					Without cap *(4)*	**ZB4 BA791**	0.056

569144


XB4 BA731327

569146


ZB4 BA73133

569148


ZB4 BA71124

Specific accessories for multiple-headed pushbuttons

Description	Background colour	Marking	Sold in lots of	Reference	Weight kg
Caps only for clip-on mounting on double or triple-headed pushbuttons *(5)*	White	Unmarked	10	**ZBA 71**	0.010
		"I" black	10	**ZBA 7131**	0.010
		"➡" black	10	**ZBA 7134**	0.010
		"+" black	10	**ZBA 7138**	0.010
	Black	Unmarked	10	**ZBA 72**	0.010
		"O" white	10	**ZBA 7232**	0.010
		"+" white	10	**ZBA 7233**	0.010
		"⇨" white	10	**ZBA 7235**	0.010
		"I" white	10	**ZBA 7237**	0.010
	Green	Unmarked	10	**ZBA 73**	0.010
		"I" white	10	**ZBA 7331**	0.010
		"+" white	10	**ZBA 7333**	0.010
		"⇧" white	10	**ZBA 7335**	0.010
		"II" white	10	**ZBA 7336**	0.010
	Red	Unmarked	10	**ZBA 74**	0.010
		"O" white	10	**ZBA 7432**	0.010
	Yellow	Unmarked	10	**ZBA 75**	0.010
	Blue	Unmarked	10	**ZBA 76**	0.010
Clear silicone boots*(6)*	For 2 flush pushes	–	10	**ZBA 708**	0.055
	For 3 pushes	–	10	**ZBA 709**	0.055
	For 1 flush push + 1 projecting push	–	10	**ZBA 710**	0.055

540585

ZBA 7235

569177

ZBA 7331

569178

ZBA 7432

540598

ZBA 709

Heads with black metal bezel

To order, add the suffix **7** to the references selected above.
Example: **ZB4 BA73132** becomes **ZB4 BA731327**.

(1) Recommended maximum number of contacts constituting the body (fixing collar + contact) associated with the head, see page 36072-EN/2.
(2) Not compatible with high power switching contacts and contacts for printed circuit board.
(3) These caps are fitted by Schneider Electric and cannot be removed (risk of damage).
(4) Caps to be ordered separately: see accessories on this page.
(5) Can be clipped-in at 90° steps, through 360°.
(6) Can be replaced without dismantling the head.

General : page 36022-EN/2
Characteristics : page 36001-EN/2
Dimensions : page 36020-EN/2

Control and signalling units Ø 22

Harmony® XB5 plastic

Multiple-headed pushbuttons, spring return

User assembly of other units, using:
body-contacts assemblies: see page 36168-EN/2
combined sub-assemblies: see page 36168-EN/8
accessories: see page 36169-EN/2


569133

XB5 AL73415


569135

ZB5 AA7121


569137

ZB5 AL7341


569139

XB5 AW73731●5


569141

ZB5 AW7A1721


569149

ZB5 AW7A3741

Double-headed pushbuttons *(1)*

Screw clamp terminal connections (Schneider Electric anti-retightening system)

Shape of head	Description	Type of contact N/O	Type of contact N/C	Colour and marking of caps *(2)*	Reference	Weight kg
Complete units						
	2 pushes (1 flush black + 1 projecting red)	1	1	White “I” on green background White “0” on red background	**XB5 AL73415**	0.053
Heads only						
	2 flush black pushes			White background + black background, unmarked	**ZB5 AA7120**	0.023
				Black “I” on white background White “0” on black background	**ZB5 AA7121**	0.023
				Green background + red background, unmarked	**ZB5 AA7340**	0.023
				White “I” on green background White “0” on red background	**ZB5 AA7341**	0.023
				Without cap *(3)*	**ZB5 AA79**	0.023
	1 flush black push 1 projecting red push			Green background + red background, unmarked	**ZB5 AL7340**	0.023
				White “I” on green background White “0” on red background	**ZB5 AL7341**	0.023

Double-headed pushbuttons + 1 white central pilot light block *(1)*

Screw clamp terminal connections (Schneider Electric anti-retightening system)

Shape of head	Description	Type of contact N/O	Type of contact N/C	Colour and marking of caps *(2)*	Pilot light voltage V	Reference	Weight kg
Complete units							
Protected LED	**1 flush black push 1 projecting red push 1 white central pilot light block**	1	1	White “I” on green background White “0” on red background	24	**XB5 AW73731B5**	0.066
					120	**XB5 AW73731G5**	0.066
					240	**XB5 AW73731M5**	0.066
Heads only *(5)*							
Protected LED	**2 flush black pushes 1 clear central pilot light** *(4)*			White background + black background, unmarked		**ZB5 AW7A1720**	0.023
				Black “I” on white background White “0” on black background		**ZB5 AW7A1721**	0.023
				Green background + red background, unmarked		**ZB5 AW7A3740**	0.023
				White “I” on green background White “0” on red background		**ZB5 AW7A3741**	0.023
				Black “⬆” on white background White “⬇” on black background		**ZB5 AW7A1724**	0.023
				Black “+” on white background Black “–” on white background		**ZB5 AW7A1715**	0.023
				Without cap *(3)*		**ZB5 AW7A9**	0.023
Protected LED	**1 flush black push 1 projecting red push 1 clear central pilot light** *(4)*			Green background + red background, unmarked		**ZB5 AW7L3740**	0.023
				White “I” on green background White “0” on red background		**ZB5 AW7L3741**	0.023

(1) *Recommended maximum number of contacts constituting the body (fixing collar + contact) associated with the head, see page 36172-EN/2.*
(2) These caps are fitted by Schneider Electric and cannot be removed (risk of damage).
(3) Caps to be ordered separately: see page opposite.
(4) Colour of centrally positioned pilot light determined by the colour of the LED incorporated in the body sub-assembly.
5) Only for use with bodies comprising a light source with integral LED.

General : page 36025-EN/2
Characteristics : page 36011-EN/2
Dimensions : page 36021-EN/2

Control and signalling units Ø 22
Harmony® XB5 plastic
Multiple-headed pushbuttons, spring return

User assembly of other units, using:
body-contacts assemblies: see page 36168-EN/2
combined sub-assemblies: see page 36168-EN/8
accessories: see page 36169-EN/2

569143


XB5 AA731327

569145


ZB5 AA73133

569147


ZB5 AA71124

Triple-headed pushbuttons *(1) (2)*
Screw clamp terminal connections (Schneider Electric anti-retightening system)

Shape of head	Description	Type of contact N/O	N/C	N/O	Colour and marking of caps *(3)*	Reference	Weight kg
Complete units							
	**2 flush black pushes + 1 central projecting red push marked "Stop" in white**	1	1	1	White "I" on green background White "II" on green background	**XB5 AA731327**	0.063
					Black "➡" on white background White "⇦" on black background	**XB5 AA711237**	0.063
Heads only							
	**2 flush black pushes + 1 central projecting red push marked "Stop" in white**				White "I" on green background White "II" on green background	**ZB5 AA73132**	0.023
					White "⇦" on green background White "⇨" on green background	**ZB5 AA73133**	0.023
					White "⇧" on green background White "⇩" on green background	**ZB5 AA73134**	0.023
					White "+" on green background White "–" on green background	**ZB5 AA73135**	0.023
					Black "+" on white background Black "–" on white background	**ZB5 AA71115**	0.023
					Black "➡" on white background White "⇦" on black background	**ZB5 AA71123**	0.023
					Black "⬆" on white background White "⇩" on black background	**ZB5 AA71124**	0.023
					White "⇧" on black background White "⇩" on black background	**ZB5 AA72124**	0.023
					Without cap *(4)*	**ZB5 AA791**	0.023

Specific accessories for multiple-headed pushbuttons

Description	Background colour	Marking	Sold in lots of	Reference	Weight kg
Caps only for clip-on mounting on double or triple-headed pushbuttons *(5)*	White	Unmarked	10	**ZBA 71**	0.010
		"I" black	10	**ZBA 7131**	0.010
		"⬆" black	10	**ZBA 7134**	0.010
		"+" black	10	**ZBA 7138**	0.010
	Black	Unmarked	10	**ZBA 72**	0.010
		"O" white	10	**ZBA 7232**	0.010
		"+" white	10	**ZBA 7233**	0.010
		"⇩" white	10	**ZBA 7235**	0.010
		"I" white	10	**ZBA 7237**	0.010
	Green	Unmarked	10	**ZBA 73**	0.010
		"I" white	10	**ZBA 7331**	0.010
		"+" white	10	**ZBA 7333**	0.010
		"⇧" white	10	**ZBA 7335**	0.010
		"II" white	10	**ZBA 7336**	0.010
	Red	Unmarked	10	**ZBA 74**	0.010
		"O" white	10	**ZBA 7432**	0.010
	Yellow	Unmarked	10	**ZBA 75**	0.010
	Blue	Unmarked	10	**ZBA 76**	0.010
Clear silicone boots *(6)*	For 2 flush pushes	–	10	**ZBA 708**	0.055
	For 3 pushes	–	10	**ZBA 709**	0.055
	For 1 flush push + 1 projecting push	–	10	**ZBA 710**	0.055

540585

ZBA 7235

569177

ZBA 7331

569178

ZBA 7432

540598

ZBA 709

(1) Recommended maximum number of contacts constituting the body (fixing collar + contact) associated with the head, see page 36172-EN/2.
(2) Not compatible with high power switching contacts and contacts for printed circuit board.
(3) These caps are fitted by Schneider Electric and cannot be removed (risk of damage).
(4) Caps to be ordered separately: see accessories on this page.
(5) Can be clipped-in at 90° steps, through 360°.
(6) Can be replaced without dismantling the head.

General : page 36025-EN/2
Characteristics : page 36011-EN/2
Dimensions : page 36021-EN/2