Product data sheet
Characteristics

NSYPAP108G
reversible internal door polyester 2 locks grid pattern forPLM108



Main

Range	Thalassa
Accessory / separate part category	Enclosure accessory
Product or component type	Door
Application	Multi-purpose
Mounting location	Front side
Range compatibility	Thalassa PLM enclosure
Device composition	1 door 1 handle 4 fixing brackets

Complementary

Material	Polyester charged with fibreglass
Colour	Grey RAL 7035
Lock type	Lock 5 mm double bar
Number of locks	2
Door type	Internal plain
Door opening	Reversible 110 °
Height	Grid pattern : 850 mm
Width	Grid pattern : 650 mm
Depth	Available depth between enclosure door : 37 mm Available depth between rear : 269 mm

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1511 - Schneider Electric declaration of conformity

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.