Product data sheet
Characteristics

08523
plain door, IP55, W = 300 mm



Main

Range	Prisma
Product name	Prisma P
IP degree of protection	IP55
Product or component type	Door
Type of front plate	Plain
Provided equipment	Polyurethane joint Black handle with lock for 405 key Hinge (x4) Other keylock and insert (to be ordered separately) Door

Complementary

Door opening side	Reversible
Door opening angle	120 °
Installation description	Cubicle duct - width 300 mm
Number of vertical modules (50 mm)	36
Enclosure material	Treated sheet steel
Quantity per set	Set of 1
Height	2000 mm
Width	300 mm
Product weight	14.76 kg
Colour	White RAL 9001

Environment

IK degree of protection	IK10 conforming to EN/IEC 62262
Standards	IEC 61439-2 IEC 61439-1
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0813 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Available Download End Of Life Manual

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.