Product data sheet
Characteristics

A9XPH557
comb busbar - Easy to cut - Acti 9 balanced 4 Poles 57 modules 100A



Main

Range	Linergy
Product name	Linergy FH
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Poles description	4P
Number of ways	28 ways for outgoer, type : N + L with 18 mm pitch
Distance between way	36 mm
Poles distribution	N L1 N L2 N L3
Connector type	Tooth
Length in 18 mm modules	57

Complementary

Device presentation	Cuttable
[In] rated current	100 A (40 °C)
[Ue] rated operational voltage	415 V AC
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2
Mounting mode	Horizontal
9 mm pitches	114
Width	1000 mm
Colour	Anthracite grey (RAL 7016)
Range compatibility	Acti 9
Product compatibility	IC60 IID ISW-NA IK60 IID K ISW switch disconnector

Environment

Standards	IEC 60947-7-1 IEC 61439-2
Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1336 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.