Product data sheet
Characteristics

NSYDLA66G
Modular distribution chassis 66 modules for NSYPLM75,NSYS3D75,NSYCRN75,NSYS3X75



Main

Range	Spacial
Accessory / separate part category	Mounting accessory
Application	Multi-purpose Modular distribution application
Product or component type	Chassis
Device short name	DLA
Mounting location	Front of enclosure
Range compatibility	Spacial S3D, CRN, S3X enclosures (except with door stop or door switch) Thalassa PLM enclosure
Device composition	1 chassis structure 2 finish cover 1 neutral/earth strip 2 x 16 mm² 5 x 6 mm² 3 front panels with 35 mm DIN rail 1 plain front panel with mounting plate
Quantity per set	Set of 1

Complementary

Material	Self-extinguishing insulating for front panel Steel for chassis structure and rails
Colour	Front panel : grey RAL 7035
Fixing mode	By fixing element - on front with supports location
Adjustment	In height from 40 to 85 mm for DIN rail
Number of horizontal rows	4
Total number of 18 mm modules	66
Type of front plate	Plain and cut-out plates
Number of cut-out	4 cut-outs
Height	680 mm
Width	460 mm

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1511 - Schneider Electric declaration of conformity

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.