

# Fuse-link, LV, 60 A, AC 600 V, 27 x 60 mm, J, UL, time-delay

**Article no.** LPJ-60SP
**Catalog No.** LPJ-60SP

Similar to illustration

## Delivery programme

| | | | |
|---|---|---|---|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 60 |
| Rated voltage | | | AC 600 V |
| Size | | | 27 x 60 mm |
| Utilization category | | | J |
| Breaking Capacity | | kA | 300 |
| Release characteristic | class | | time-delay |
| Standard/Approval | | | UL |
| Time delay | | | time-delay 10 seconds (minimum) at 500% of rated current |

## Technical data ETIM 6.0

| | | | |
|---|---|---|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012]) | | | |
| Construction size | | | - |
| Nominal rated current | | A | 60 |
| Nominal rated voltage | | V | 600 |
| Utilization category | | | - |
| Type of fuse status indicator | | | None |

## Additional product information (links)

| | |
|---|---|
| Product datasheet (PDF) | http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1006_LPJ_0-60.pdf |
| Product overview (WEB) | http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/fuses_class_cc_j_rk1_rk5/class_j/lpj-sp.html |


© 09/2016 by Eaton Industries GmbH