SIEMENS

Show actual product details

Data sheet 3NC8431-0C

SITOR fuse link, with slotted blade contacts, NH3, In: 350 A, gR, Un AC: 690 V, Un DC: 440 V, Front indicator



Model		
product brandname		SENTRON
Design of an identification indicator		front indicator
Design of the fuse link		SITOR, LV HRC design
General technical data		
Size of fuse system / acc. to DIN EN 60269-1		NH3
Operating class of the fuse link		gR
circuit-breaker / Design		3NC
Varying load factor (WL)		0.85
Supply voltage / at DC	V	440
Switching capacity		
Switching capacity current		
• acc. to IEC 60947-2 / rated value	kA	100
Dissipation		
Power loss [W]		
• for rated value of the current / at AC / in hot operating state / per pole	W	95
• maximum	W	95

Subject to change without notice
© Copyright Siemens AG

Electricity		
rated current In / IEC, DIN/VDE / at 40 Cel	A	350
Current / at AC / rated value	A	350

Mechanical Design		
Mounting position		Any, preferably vertical

Environmental conditions		
Ambient temperature		
• minimum	°C	-20
• maximum	°C	50
Environmental category		-20 to +50 at 95% relative humidity

Certificates		
Equipment marking		
• acc. to DIN EN 61346-2		F
• acc. to DIN EN 81346-2		F

General Product Approval		Declaration of Conformity
EAC	sonstig	CE EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)
https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3NC8431-0C


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
http://support.automation.siemens.com/WW/view/en/3NC8431-0C/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC8431-0C

CAx-Online-Generator
http://www.siemens.com/cax

Tender specifications
http://www.siemens.com/specifications

Subject to change without notice
© Copyright Siemens AG



Subject to change without notice
© Copyright Siemens AG