

Fuse-link, LV, 20 A, AC 400 V, D02, aR, IEC, ultra rapid

Article no. 20NZ02R
Catalog No. 20NZ02R

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	20
Rated voltage			AC 400 V
Construction size			D02
Utilization category			aR
usable for size/applications			E18 for domestic and general industrial applications
Release characteristic	class		ultra rapid
Standard/Approval			IEC
Standards/Regulations			IEC 60269-3 VDE 0636

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / DO-system fuse link (EC001642)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Neozed fuse link (ecl@ss8.1-27-14-21-19 [ACN353008])

Construction size			D02
Nominal rated current		A	20
Nominal rated voltage		V	400
Colour code			Blue
Utilization category			aR (accompanied semiconductor protection)

Additional product information (links)

Product datasheet (PDF)	http://www.cooperindustries.com/content/dam/public/bussmann/iec-electrical/resources/data-sheets/bus-iec-ds-4124-danddofuselinks.pdf

© 12/2016 by Eaton Industries GmbH