

Fuse-link, high speed, 25 A, AC 700 V, 22 x 58 mm, aR, UL

Article no. FWP-25A22F
Catalog No. FWP-25A22F

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	25
Rated voltage			AC 700 V
Size			22 x 58 mm
Utilization category			aR
Breaking Capacity		kA	200
usable for size/applications			protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			UL
Shape			cylindrical
Standards/Regulations			UL 248
Optional accessories			fuse-holder CH221B

Technical data ETIM 5.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss8-27-14-20-02 [AFZ797009])			
Size			22x58 mm
Rated voltage			-
Nominal current		A	25
With striker			No

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbussmann.com/pdf/f9dd7ab4-d791-46d2-b0b4-0edba1e95df3.pdf

© 12/2016 by Eaton Industries GmbH