


# Fuse-link, high speed, 100 A, AC 700 V, 22 x 58 mm, aR, UL

Powering Business Worldwide

**Article no.** FWP-100A22F
**Catalog No.** FWP-100A22F

## Delivery program

| | | | |
|---|---|---|---|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | high speed |
| Rated current | I | A | 100 |
| Rated voltage | | | AC 700 V |
| Size | | | 22 x 58 mm |
| Utilization category | | | aR |
| Breaking Capacity | | kA | 200 |
| usable for size/applications | | | protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters |
| Standard/Approval | | | UL |
| Shape | | | cylindrical |
| Standards/Regulations | | | UL 248 |
| Optional accessories | | | fuse-holder CH221B |

## Technical data ETIM 5.0

| | | | |
|---|---|---|---|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss8-27-14-20-02 [AFZ797009]) | | | |
| Size | | | 22x58 mm |
| Rated voltage | | | - |
| Nominal current | | A | 100 |
| With striker | | | No |

## Additional product information (links)

| | |
|---|---|
| Product datasheet (pdf) | http://www1.cooperbussmann.com/pdf/f9dd7ab4-d791-46d2-b0b4-0edba1e95df3.pdf |


© 12/2016 by Eaton Industries GmbH