

# Fuse-link, high speed, 15 A, AC 700 V, 14 x 51 mm, aR, UL, with striker

**Article no.** FWP-15A14FI
**Catalog No.** FWP-15A14FI

Similar to illustration

## Delivery program

| | | | |
|---|---|---|---|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | high speed |
| Rated current | I | A | 15 |
| Rated voltage | | | AC 700 V |
| Size | | | 14 x 51 mm |
| Utilization category | | | aR |
| Status indicator | | | with striker |
| Breaking Capacity | | kA | 200 |
| usable for size/applications | | | protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters |
| Standard/Approval | | | UL |
| Shape | | | cylindrical |
| Standards/Regulations | | | UL 248 |
| Optional accessories | | | fuse-holder CH141B |

## Technical data ETIM 5.0

| | | | |
|---|---|---|---|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss8-27-14-20-02 [AFZ797009]) | | | |
| Size | | | 14x51 mm |
| Rated voltage | | | - |
| Nominal current | | A | 15 |
| With striker | | | No |

## Additional product information (links)

| | |
|---|---|
| Product datasheet (pdf) | http://www1.cooperbussmann.com/pdf/180d391e-9852-4aa1-b086-5ce2c5cb36b4.pdf |


© 12/2016 by Eaton Industries GmbH