

Fuse-link, high speed, 50 A, AC 700 V, 14 x 51 mm, aR, UL, with striker

Article no. FWP-50A14FI
Catalog No. FWP-50A14FI

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	50
Rated voltage			AC 700 V
Size			14 x 51 mm
Utilization category			aR
Status indicator			with striker
Breaking Capacity		kA	200
usable for size/applications			protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			UL
Shape			cylindrical
Standards/Regulations			UL 248
Optional accessories			fuse-holder CH141B

Technical data ETIM 5.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss8-27-14-20-02 [AFZ797009])			
Size			14x51 mm
Rated voltage			-
Nominal current		A	50
With striker			No

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbussmann.com/pdf/180d391e-9852-4aa1-b086-5ce2c5cb36b4.pdf

© 12/2016 by Eaton Industries GmbH