

# Fuse-link, LV, 0.125 A, AC 600 V, 10 x 38 mm, CC, UL, fast acting, rejection-type

Powering Business Worldwide

**Article no.** KTK-R-1-8
**Catalog No.** KTK-R-1/8

Similar to illustration

## Delivery program

| | | | |
|---|---|---|---|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 0.125 |
| Rated voltage | | | AC 600 V |
| Size | | | 10 x 38 mm |
| Utilization category | | | CC |
| Description | | | rejection-type |
| Breaking Capacity | | kA | 200 |
| usable for size/applications | | | branch circuit |
| Release characteristic | class | | fast-acting |
| Standard/Approval | | | UL |
| Shape | | | cylindrical |

## Technical data ETIM 6.0

| | | | |
|---|---|---|---|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss8.1-27-14-20-02 [AFZ797010]) | | | |
| Size | | | 10x38 mm |
| Rated voltage | | | AC 600 V |
| Nominal current | | A | 0.125 |
| With striker | | | No |

## Additional product information (links)

| | |
|---|---|
| Product datasheet (PDF) | http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1015_KTK-R.pdf |
| Product overview (WEB) | http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/fuses_class_cc_j_rk1_rk5/class_cc/ktk-r1.html |


© 12/2016 by Eaton Industries GmbH