

Fuse-link, high speed, 160 A, AC 690 V, DIN 000, aR, DIN, IEC, dual indicator, live gripping lugs

Powering Business Worldwide

Article no. 170M1569D
Catalog No. 170M1569D

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	160
Rated voltage			AC 690 V
Construction size			DIN 000
Utilization category			aR
Status indicator			dual (combination) indicator system
Description			live gripping lugs indicator style T for microswitch
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with knife blade contacts
Standards/Regulations			DIN 43620 IEC 60269-4
Optional accessories			microswitches 170H0238, 170H0236

Technical data ETIM 5.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8-27-14-20-05 [AFZ800011])

Construction size			-
Rated current		A	160
Rated voltage		V	690
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Combination fuse status indicator

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbussmann.com/pdf/9f923efa-8988-4587-86ef-83187b477d49.pdf

© 02/2017 by Eaton Industries GmbH