

# Fuse-link, high speed, 315 A, AC 690 V, DIN 1, aR, DIN, IEC, dual indicator, live gripping lugs

Powering Business Worldwide

**Article no.** 170M3817D
**Catalog No.** 170M3817D

## Delivery program

| | | | |
|---|---|---|---|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | high speed |
| Rated current | I | A | 315 |
| Rated voltage | | | AC 690 V |
| Construction size | | | DIN 1 |
| Utilization category | | | aR |
| Status indicator | | | dual (combination) indicator system |
| Description | | | live gripping lugs<br>indicator style T for microswitch |
| Breaking Capacity | | kA | 200 |
| usable for size/applications | | | semiconductor protection |
| Standard/Approval | | | DIN<br>IEC |
| Shape | | | square body with knife blade contacts |
| Standards/Regulations | | | DIN 43620<br>IEC 60269-4 |

## Technical data ETIM 5.0

| | | | |
|---|---|---|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8-27-14-20-05 [AFZ800011]) | | | |
| Construction size | | | - |
| Rated current | | A | 315 |
| Rated voltage | | V | 690 |
| Utilization category | | | aR (accompanied semiconductor protection) |
| Type of fuse status indicator | | | Combination fuse status indicator |

## Additional product information (links)

| | |
|---|---|
| Product datasheet (pdf) | http://www1.cooperbussmann.com/pdf/ca1a6bc7-bb6b-44a1-9c84-9b553fae7f8c.pdf |


© 02/2017 by Eaton Industries GmbH