# Product data sheet
## Characteristics

# 08115
## extension enclosure W600 15M Prisma G IP30



## Main

| | |
|---|---|
| Range | Prisma |
| Product name | Prisma G |
| IP degree of protection | IP30 without door conforming to EN/IEC 60529<br>IP40 with door<br>IP41 with door and canopy<br>IP43 with door, canopy and IP43 gasket |
| Product or component type | Enclosure extension |
| Enclosure type | Functional enclosure delivered in kit form |
| Device application | Low voltage electrical distribution |
| Enclosure mounting | Surface |
| Type of front cover | Without (to be ordered separately) |
| Product compatibility | Wall-mounted enclosure - width 600 mm |
| Number of vertical modules (50 mm) | 15 |
| Number of 18 mm modules per row | 24 |

## Complementary

| | |
|---|---|
| Enclosure/Cubicle description | Wall-mounted enclosure - width 600 mm |
| [Ui] rated insulation voltage | 1000 V on main rear busbars conforming to IEC 61439-2 |
| [In] rated current | 630 A at 40 °C conforming to IEC 61439-2 |
| [Icw] rated short-time withstand current | 25 kA (1 s) conforming to IEC 61439-2 |
| [Ipk] rated peak withstand current | 53 kA conforming to IEC 61439-2 |
| Network frequency | 50/60 Hz |
| Enclosure material | Enclosure : treated sheet steel |
| Additional information | Can be combined side by side and one on top of another |
| Quantity per set | Set of 1 |
| Height | 780 mm |
| Width | 600 mm |
| Depth | 205 mm |
| Surface finish | Matt<br>Smooth |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| Colour | White RAL 9001 |

## Environment

| | |
|---|---|
| IK degree of protection | IK07 without door conforming to EN/IEC 62262<br>IK08 with door |
| Protective treatment | Electrophoresis treatment and hot-polymerised polyester epoxy powder |
| Standards | IEC 62208<br>IEC 61439-1<br>IEC 61439-2 |
| Mechanical robustness | Seismic tests : 2G conforming to IEC 60068-2-57 |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Will be compliant on 2Q2016<br>Will be compliant on 2Q2016 |
| REACh | Reference not containing SVHC above the threshold<br>Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |