

Fuse-holder, LV, 32 A, DC 1000 V, 10 x 38 mm, gPV, 1P, UL, IEC, indicating, DIN rail mount

Powering Business Worldwide

Article no. CHPV1IU
Catalog No. CHPV1IU

Delivery program

Product range			Fuse accessory
Basic function			Fuse-holder
Field of application			low voltage
Rated current	I	A	32
Rated voltage			DC 1000 V
Size			10 x 38 mm
Utilization category			gPV
Status indicator			with indicator
Description			DIN rail mounting Modular colour-coded Rated for use with 75°C or 90°C wire, fine stranded wire, spade terminals and with comb-bus bars. Use any higher temperature rated wire with appropriate derating.
Number of poles			1P
usable for size/applications			Photovoltaic for cylindrical fuse-links
Standard/Approval			UL IEC
Standards/Regulations			IEC cULus CCC CSA UR

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Holder for cylindrical fuse (EC002705)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Holder for cylindrical fuse (ecl@ss8.1-27-14-21-21 [ADI305004])			
For fuse size			10x38 mm
Number of poles			1
Concurrently switching N-neutral			No

Additional product information (links)

Product datasheet (PDF)	http://www1.cooperbussmann.com/pdf/84e185ef-62d9-48ca-b609-a65353c730ce.pdf

© 02/2017 by Eaton Industries GmbH