

Fuse-link, LV, 500 A, AC 690 V, NH3, aM, IEC, dual indicator, live gripping lugs

Powering Business Worldwide

Article no. 500NHM3B-690
Catalog No. 500NHM3B-690

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	500
Rated voltage			AC 690 V
Construction size			NH3
Utilization category			aM
Status indicator			dual (combination) indicator system
Description			live gripping lugs
Breaking Capacity		kA	120
Standard/Approval			IEC
Shape			square body with knife blade contacts
Standards/Regulations			IEC 60269-2 fuse system A DIN 43620 VDE 0636-2

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			NH3
Nominal rated current		A	500
Nominal rated voltage		V	690
Utilization category			aM (switchgear protection)
Type of fuse status indicator			Combination fuse status indicator

Additional product information (links)

Product datasheet (PDF)	http://www1.cooperbussmann.com/pdf/eb30bb45-9850-4820-a3b9-8e873de29a03.pdf

© 02/2017 by Eaton Industries GmbH