Product data sheet
Characteristics

KBC10DCB20
Canalis - tap-off unit - 10 A - phase selection - without protection - L+N+PE



Main

Range of product	Canalis
Product or component type	Tap-off unit
Device short name	KBC
Product compatibility	KBA KDP KBB

Complementary

Device application	Lighting
[Ue] rated operational voltage	230...240 V
[Ui] rated insulation voltage	690 V
[Ie] rated operational current	10 A at 35 °C
Network frequency	50/60 Hz
Protection type	Without protection
Busbar trunking polarity	L1 + N + PE L2 + L1 + L3 + PE L2 + N2 + L3 + PE
Tap-off unit polarity	L2+L3 L1+L2 L2+N L1+N L3+N3 L2+N2 L3+N L1+L3
Tap-off unit connector type	With phase selection
Standards	EN/IEC 60439-2 EN/IEC 61439-6
Width	1 m
Depth	62 mm
Height	60 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product weight	65 g
Quantity per set	Set of 10

Environment

IP degree of protection	IP55 conforming to EN/IEC 60529

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0801 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference contains SVHC above the threshold - Go to CaP for more details Go to CaP for more details
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations Product environmental

Contractual warranty

Warranty period	18 months