

Fuse-link, low voltage, 50 A, AC 600 V, DC 300 V, 26 x 29 x 55 mm, CF, J, 1P, UL, CSA, time-delay

Powering Business Worldwide

Article no. TCF50
Catalog No. TCF50

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	50
Rated voltage			AC 600 V DC 300 V
Size			26 x 29 x 55 mm
Utilization category			CF J
Description			finger-safe
Breaking Capacity		kA	300
Number of poles			1P
Release characteristic	class		time-delay
Standard/Approval			UL CSA
Time delay			time-delay 10 seconds (minimum) at 500% of rated current

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			-
Nominal rated current		A	50
Nominal rated voltage		V	600
Utilization category			-
Type of fuse status indicator			None

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_9000_TCF_TCF_RN.pdf
Product datasheet (web)	http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/supplemental/class_cf_cubefuse/tcf_tcf-rn_fuse_tcfh-nholder.html

© 03/2017 by Eaton Industries GmbH