# WALL MOUNTING WATERTIGHT MODULAR ENCLOSURES - IP65 - RAL 7035



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 62004** | GC | PCS | 4 modules | 1/22 |
| **EC 62008** | GC | PCS | 8 modules | 1/14 |
| **EC 62012** | GC | PCS | 12 modules | 1/8 |
| **EC 62024** | GC | PCS | 24 modules (2x12) | 1 |
| **EC 62036** | GC | PCS | 36 modules (2x18) | 1 |
| **EC 62054** | GC | PCS | 54 modules (3x18) | 1 |
| **EC 62072** | GC | PCS | 72 modules (4x18) | 1 |

BLANK PLATE FOR 72 MODULES ENCLOSURE



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 67018** | GC | PCS | blank plate 18 modules for 62072 | 1/10 |

PLASTIC BRACKET



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 600SF** | GC | PCS | plastic bracket to keep IP-protection and double insulation - for all enclosures series 620-640 | 50 |

INSTALLATION KIT FOR WALL MOUNTING WATERTIGHT MODULAR ENCLOSURES



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 6204EQ** | | PCS | for 4 modules | 1/22 |
| **EC 6208EQ** | | PCS | for 8 modules | 1/14 |
| **EC 6212EQ** | | PCS | for 12 modules | 1/8 |
| **EC 6224EQ** | | PCS | for 24 modules | 1 |
| **EC 6236EQ** | | PCS | for 36 modules | 1 |
| **EC 6254EQ** | | PCS | for 54/72 modules | 1 |

SAFETY LOCK



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 600SC** | | PCS | lock and 2 keys | 1 kit |

The keys are unified and open all the locks.

# WALL MOUNTING WATERTIGHT EMERGENCY MODULAR ENCLOSURES - IP65




| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 64004** | R | PCS | 4 modules - red | 1/22 |
| **EC 64008** | R | PCS | 8 modules - red | 1/14 |
| **EC 64104** | GC | PCS | 4 modules - grey | 1/22 |
| **EC 64108** | GC | PCS | 8 modules - grey | 1/14 |
| **EC 64401** | | PCS | spare glass 4 modules | 10 |
| **EC 64402** | | PCS | spare glass 8 modules | 10 |

# BREAKING GLASS EMERGENCY PANEL - IP55



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 64202** | R | PCS | call point 1NO+1NC | 1 |

## EMERGENCY CALL POINT ACCESSORIES



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 64400** | | PCS | stell glass hammer with safety chain | 1 |
| **EC 64403** | | PCS | spare glass dim. 78x76x1,85 mm | 10 |

## SPARE CONTACT



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 64410** | | PCS | spare contact NC red | 10 |
| **EC 64411** | | PCS | spare contact NO green | 10 |

## LAMP HOLDER WITH LED



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 64420** | | PCS | AC/DC 12V - white light | 10 |
| **EC 64421** | | PCS | AC/DC 24V- white light | 10 |
| **EC 64422** | | PCS | AC/DC 48V- white light | 10 |
| **EC 64423** | | PCS | AC/DC 110V- white light | 10 |
| **EC 64424** | | PCS | AC 220V- white light | 10 |

## STANDARD LAMP - BLUE LIGHT



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC L4000LN** | | PCS | neon AC 220V | 10 |
| **EC L4000LD** | | PCS | LED AC 220V | 10 |

COLOURS: **B**=WHITE RAL 9001, **GC**=GREY RAL 7035, **R**=RED RAL 3000, **N**=BLACK, **AR**=ORANGE, **G**=YELLOW, **BL**=BLUE

NEW

# TECHNICAL SPECIFICATION

Possibility to mount 45-78 mm high modules

The transparent door is removable, and the front is reversible

Kits of brass terminals specific for every model, easy to install



Strong enclosure structure with stiffening outer ring

Cover for unused modules included

Cable inlet by corrugated conduits up to 40 mm

The supports of the DIN-rails permit to compensate for the variable thickness of the plaster in order to align the devices at the correct depth

Self-adhesive circuit labels

The range of flush mounting modular enclosures is wide and complete: it comprises enclosures from 4 up to 72 modules available in different colours, such as grey, black, white with transparent smoky grey and white with solid door. They are suitable both for the industrial applications and for the domestic and public environments, in which the domotics plays a very important role nowadays.

The enclosures, made up of orange polystyrene, have a high mechanical strength, so that they don't get deformed during the installation; besides, they are characterized by pre-cuttings for the conduit inlet up to 40 mm.
Both the bottom and the front are perfectly symmetric, so that there is no top or bottom to pay attention to during the installation.
The reversible front permits to open the door at more than 180° either right or left.
The stainless steel DIN rail EN50022 can be horizontally adjusted to perfectly line up the equipments and devices.
The support rails are so designed to compensate for the variable thickness of the plaster in order to align the devices at the correct depth.

## FLUSH MOUNTING MODULAR ENCLOSURES WITH TRANSPARENT DOOR - IP40 - RAL 7035



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 63004** | GC | PCS | 4 modules | 1/20 |
| **EC 63008** | GC | PCS | 8 modules | 1/9 |
| **EC 63012** | GC | PCS | 12 modules | 1/7 |
| **EC 63024** | GC | PCS | 24 modules (2x12) | 1 |
| **EC 63036** | GC | PCS | 36 modules (2x18) | 1 |
| **EC 63054** | GC | PCS | 54 modules (3x18) | 1 |
| **EC 63072** | GC | PCS | 72 modules (4x18) | 1 |

## FLUSH MOUNTING MODULAR ENCLOSURES WITH TRANSPARENT DOOR - IP40 - RAL 9001



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 63004B** | B | PCS | 4 modules | 1/20 |
| **EC 63008B** | B | PCS | 8 modules | 1/9 |
| **EC 63012B** | B | PCS | 12 modules | 1/7 |
| **EC 63024B** | B | PCS | 24 modules (2x12) | 1 |
| **EC 63036B** | B | PCS | 36 modules (2x18) | 1 |
| **EC 63054B** | B | PCS | 54 modules (3x18) | 1 |
| **EC 63072B** | B | PCS | 72 modules (4x18) | 1 |

## FLUSH MOUNTING MODULAR ENCLOSURES WITH SOLID DOOR - IP40 - RAL 9001



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 63004C** | B | PCS | 4 modules | 1/20 |
| **EC 63008C** | B | PCS | 8 modules | 1/9 |
| **EC 63012C** | B | PCS | 12 modules | 1/7 |
| **EC 63024C** | B | PCS | 24 modules (2x12) | 1 |
| **EC 63036C** | B | PCS | 36 modules (2x18) | 1 |
| **EC 63054C** | B | PCS | 54 modules (3x18) | 1 |
| **EC 63072C** | B | PCS | 72 modules (4x18) | 1 |

## FLUSH MOUNTING MODULAR ENCLOSURES WITH TRANSPARENT DOOR - IP40 - BLACK



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 63004N** | N | PCS | 4 modules | 1/20 |
| **EC 63008N** | N | PCS | 8 modules | 1/9 |
| **EC 63012N** | N | PCS | 12 modules | 1/7 |
| **EC 63024N** | N | PCS | 24 modules (2x12) | 1 |
| **EC 63036N** | N | PCS | 36 modules (2x18) | 1 |
| **EC 63054N** | N | PCS | 54 modules (3x18) | 1 |
| **EC 63072N** | N | PCS | 72 modules (4x18) | 1 |

## DRY LINING MODULAR DISTRIBUTION ENCLOSURES WITH TRANSPARENT DOOR IP40 - RAL 9001



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 63508B** | B | PCS | 8 modules | 1/9 |
| **EC 63512B** | B | PCS | 12 modules | 1/7 |
| **EC 63524B** | B | PCS | 24 modules (2x12) | 1 |

NEW

# WALL BOX FOR ELECTRICAL DEVICES "MYLIFE" SYSTEM OR SIMILAR - **IP44**



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC L5610A1** | GC | PCS | 1 device | 1/60 |
| **EC L5610A2** | GC | PCS | 2 devices | 1/60 |
| **EC L5610A3** | GC | PCS | 3 devices | 1/40 |
| **EC L5610A4** | GC | PCS | 4 devices | 1/30 |
| **EC L5610A6** | GC | PCS | 6 devices | 1/18 |

# WALL BOX FOR ELECTRICAL DEVICES "MYLIFE" SYSTEM OR SIMILAR - **IP55**



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC L5611A1** | GC | PCS | 1 device | 1/50 |
| **EC L5611A2** | GC | PCS | 2 devices | 1/50 |
| **EC L5611A3** | GC | PCS | 3 devices | 1/35 |
| **EC L5611A4** | GC | PCS | 4 devices | 1/25 |
| **EC L5611A6** | GC | PCS | 6 devices | 1/15 |

On request all “MYLIFE” sockets or devices mounted.

INSTALLATION KIT FOR FLUSH MOUNTING MODULAR ENCLOSURES



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 6304EQ** | | PCS | for 4 modules | 1/20 |
| **EC 6308EQ** | | PCS | for 8 modules | 1/9 |
| **EC 6312EQ** | | PCS | for 12 modules | 1/7 |
| **EC 6324EQ** | | PCS | for 24 modules | 1/5 |
| **EC 6336EQ** | | PCS | for 36 modules | 1/4 |
| **EC 6354EQ** | | PCS | for 54/72 modules | 1 |

BLANK PLATE FOR 72 MODULES ENCLOSURE



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 67018** | GC | PCS | blank plate 18 modules for 63072 | 1/10 |

MODULAR BLANK PLATE - 4,5 MODULES



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 600TC** | GC | PCS | 4,5 modules - grey | 25 |
| **EC 600TCB** | B | PCS | 4,5 modules - white | 25 |
| **EC 600TCR** | R | PCS | 4,5 modules - red | 25 |
| **EC 600TCN** | N | PCS | 4,5 modules - black | 25 |

TERMINAL BLOCK PLASTIC SUPPORTS



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 67004** | GC | PCS | for 4-8 | 10 |
| **EC 67012** | GC | PCS | for 12-24-36-54-72 | 10 |

BRASS TERMINAL BLOCKS



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 680M1** | | PCS | 4x25 | 10 |
| **EC 680M2** | | PCS | 2x25-6x10 | 10 |
| **EC 680M3** | | PCS | 2x25-10x10 | 10 |
| **EC 680M4** | | PCS | 1x25+4x16 | 10 |
| **EC 680M5** | | PCS | 1x25+6x16 | 10 |
| **EC 680M6** | | PCS | 1x25+8x16 | 10 |

INSULATED BRASS TERMINAL BLOCK TO BE SET ON DIN EN 50022 RAIL



| ITEM | COLOUR | UM | DESCRIPTION | PACK-AGING |
|---|---|---|---|---|
| **EC 890050** | | PCS | 1x35+ 6x16-blue | 10/340 |
| **EC 890051** | | PCS | 1x35+1x25+ 10x16-blue | 10/320 |
| **EC 890052** | | PCS | 1x35+2x25+ 12x16-blue | 10/240 |
| **EC 890053** | | PCS | 1x35+ 6x16-green | 10/340 |
| **EC 890054** | | PCS | 1x35+1x25+ 10x16-green | 10/320 |
| **EC 890055** | | PCS | 1x35+2x25+ 12x16-green | 10/240 |
| **EC 890056** | | PCS | 1x35+ 6x16-black | 10/340 |
| **EC 890057** | | PCS | 1x35+1x25+ 10x16-black | 10/320 |
| **EC 890058** | | PCS | 1x35+2x25+ 12x16-black | 10/240 |



COLOURS: **B**=WHITE RAL 9001, **GC**=GREY RAL 7035, **R**=RED RAL 3000, **N**=BLACK, **AR**=ORANGE, **G**=YELLOW, **BL**=BLUE