WALL MOUNTING EMERGENCY PUSH-BUTTON

MAIN TECHNICAL FEATURES:

- Material: made of shock resistant halogen free technopolymer on ABS base or aluminum.
- Standard colour: grey RAL 7035.
- Shock resistance: IK08 (up to 6 j).
- Resistance to abnormal heat: up to 650°C (Glow Wire Test according to IEC 60695-2-11 standard).
- Rated operational voltage Ue: 250V
- Contact NA 10A.
- IP65 protection degree.
- Application temperature: minimum –5°, maximum +60°.
- Preparing for conduit entry Ø 20/25 mm.
- Made in compliance with : EN418, EN60947-5-1, EN 60204-1, ISO 13850 standards

IP65

CE

GREY RAL 7035

Wall mounting emergency push-button

ITEM	DESCRIPTION	DIMENSIONS mm	PACKAGING PIECES
EC69000E	Ø 40 mm - twist to release	96x96x105	1/12 pcs
EC69000ES	Ø 40 mm - twist to release with vision red/green	96x96x105	1/12 pcs
EC69003E	Ø 40 mm - push-pull	96x96x105	1/12 pcs
EC69003EL	Ø 40 mm - push-pull with lens cap	96x96x105	1/12 pcs
EC69007E	Ø 40 mm - with key release	96x96x105	1/12 pcs
EC69000EAL	Ø 40 mm - twist to release - aluminum box	100x100x59	1/12 pcs
EC69060E	Ø 60 mm - twist to release	96x96x105	1/12 pcs
EC69063E	Ø 60 mm - push-pull	96x96x105	1/12 pcs



EC69000E



EC69000ES



EC69003E



EC69003EL



EC69007E



EC69060E



EC69063E



EC69000EAL