LAPP GROUP	**DATA SHEET**	10399800
	EPIC® MCS/MCB 3CM-HV MODULE HIGH VOLTAGE 3 POLE	Valid from: 13.07.2015

Description

- The mixed assembly guarantees high flexibility. For applications in mechanical and plant engineering, for printing machines and slide-in technology.
- Assembly of individual connectors, suitable for different applications



General Characteristics

Series	MC Module
Number of Contacts	3
Termination Methods	Crimp termination: 0.5 – 10.0 mm²
Temperature Range	-40°C to +100°C, short-term up to +125°C

Artikel No.	Module	VPE
10399800	Male	10
10399900	Female	10

Mechanical Characteristics

Cycles of mechanical operation	100

Electrical Characteristics

Rated Voltage	1000 V
Rated Current	50 A
Contact resistance	< 2 mOhm
Pollution Degree	3

Materials and Surfaces

Contact	Copper alloy, hard silver-plated
Module	PA
Flammability Class according to UL 94	V0

Approvals

UL-Approval, E-File-Number	E75770

Standard

Product Standard	IEC 61984, UL 1977

We reserve all rights according to DIN ISO 16016.

MAST1 / 04.05.2016 / freigegeben

Technical Drawing







Automation

Industrial machinery and plant engineering

Wind Energy

Info

Power and signal modules can be used together in one housing

Application range

Plant engineering
Printing machines
Control engineering

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

We reserve all rights according to DIN ISO 16016.

MAST1 / 04.05.2016 / freigegeben