Mosaic™ Programme mechanisms

data and telephone sockets


0 765 35


0 786 17


0 787 66


0 787 61


0 787 32

Selection chart for boxes, supports and plates **p. 804-805**

RJ 45 doubler sockets

Pack	Cat.Nos	
		1 module
		Ethernet/Ethernet
10	0 765 39	FTP - 9 contacts
10	0 765 38	UTP - 8 contacts
		Telephone/Ethernet
10	0 765 37	FTP - 9 contacts
10	0 765 36	UTP - 8 contacts
		Telephone/telephone
10	0 765 35	45 contacts

Adaptors for RJ 45 connector

Equipped with transparent marker holder
White - 2 modules

10	0 786 04	For single Keystone connector
10	0 786 10	For 2 Keystone connectors
10	0 786 02	For single Systimax connector
10	0 786 03	For double Systimax connector
10	0 786 09	For single Infra⁺ connector
10	0 786 11	For single Ortronics connector
10	0 786 12	For double Ortronics connector

Optical sockets - 2 modules

For connecting 2 fibres to the workstation
Equipped with 1 duplex adaptor
Supplied with protective caps

1	0 786 14	SC/APC single mode fiber optic socket
1	0 786 16	Socket with 2 ST optical adaptors bayonet connection
1	0 786 17	Socket with 2 SC optical adaptors push-pull connection
1	0 786 18	Socket with 2 LC optical adaptors push-pull connection

SUB D sockets - 2 modules

1	0 787 65	9 contacts - Screw terminals connection to link type RS 232 series
1	0 787 67	9 contacts - Soldering connection to link type RS 232 series
1	0 787 66	15 contacts - Soldering connection For example used for specialized line type X21 between 2 distant devices

Female USB data sockets - for data transfer

Used to bring connections closer to the user
For connecting USB devices (scanner-printer, external hard disk)
Max. cable length: 5 m. Recommended cable: USB A
1 module

Preterminated
USB 3.0. Equipped with a 15 cm cord

1	0 787 46	○ White

Connection via screw terminals
USB 2.0. Cross-section: 1 mm²

1	0 787 61	○ White
1	0 792 84	● Alu

Female USB amplifier - for data transfer

Used to bring connections closer to the user in case of large distances
For connecting USB devices (digital school board / interactive whiteboard…) located more than 5 m away from a source (computer…)
The kit includes a transmitter (1 module) and a receiver (1 module). The link between the transmitter and the receiver is made via a RJ 45 / RJ 45 cord

1	0 787 48	○ White

Telephone sockets

RJ 11 and RJ 12 sockets
Equipped with a modular Jack connector with 1/4 turn terminal for fast connection. Tap-off possible

10	0 787 30	○ White - RJ 11, 4 contacts - 1 module
10	0 792 31	● Alu - RJ 11, 4 contacts - 1 module
10	0 787 31	○ White - RJ 11, 4 contacts - 2 modules
10	0 787 32	○ White - RJ 12, 6 contacts - 2 modules

ISDN socket
Self-stripping 1/4 turn terminals for fast connection
Tap-off possible

10	0 787 34	○ White - 8 contacts, 2.5 mm² earth terminal

Flush-mounting telephone/Ethernet double connectors

Provide increased security against theft and damage to double connectors
Provide a rate of 10/100 Mbps
Multidirectional cable entry
Can be installed in all supports min. 35 mm deep
Telephone and Ethernet applications marked on the protective flap
9 contacts - 1 module - White

10	0 765 37	FTP
10	0 765 36	UTP