SIEMENS

Data sheet 8WD4428-6XF

LED, Base BA 15d, blue, 24 V AC/DC, accessory for signaling columns, with diameters 50 mm and 70 mm



Figure similar

General technical data	
Product brand name	SIRIUS
Product designation	LED
Type of voltage of the operating voltage	AC/DC
Operating voltage	
• 1 at DC rated value	24 V
• 1 at AC at 50 Hz rated value	24 V
• 1 at AC at 60 Hz rated value	24 V
Relative positive tolerance of the operating voltage	10 %
Relative negative tolerance of the operating voltage	-15 %
Consumed current maximum	15 mA
Color	blue
• Reference indentifier acc. to DIN EN 61346-2	P
• Reference identifier acc. to DIN EN 81346-2	P

Mechanical data	
Outer diameter of the signal column element	70 mm

Subject to change without notice
© Copyright Siemens

Lamp

Type of light source	LED
Light intensity	0.21 cd
Mounting type	BA 15d

Ambient conditions

Ambient temperature during operation	-20 ... +60 °C
Height	45 mm
Width	20 mm

Certificates/approvals

General Product Approval	EMC	Declaration of Conformity	other
UL EAC C-Tick EG-Konf.			Confirmation

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WD4428-6XF

Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=8WD4428-6XF

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/8WD4428-6XF

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=8WD4428-6XF&lang=en

last modified: 01/16/2018

Subject to change without notice
© Copyright Siemens