# PATRZ KARTA - SPPVT2-10-2+PE-AX



Abbildung ähnlich

**Ogranicznik przepięć typ 2 1000VDC z sygn.**

| | |
|---|---|
| **Typ** | **SPPVT2-10-2+PE-AX** |
| **Catalog No.** | **176089** |

Powering Business Worldwide

## Program dostaw

| | | | |
|---|---|---|---|
| Asortyment | | | Ochrona przepięciowa DC |
| Produkty | | | Ograniczniki przepięć |
| Obszar zastosowania | | | Budynki mieszkalne<br>Budynki użytkowe<br>Otwarte powierzchnie |
| Opis | | | wtykany<br>z modułem wyłącznika pomocniczego |
| Podłączenie | | | do systemów bez uziemienia |
| Maximum uninterrupted voltage | $U_c$ | V | 1000 |

## Świadectwo typu zgodnie z IEC/EN 61439

| | | | |
|---|---|---|---|
| Dane techniczne dla zaświadczenia rodzaju konstrukcji | | | |
| Znamionowy prąd pracy do podania straty mocy | $I_n$ | A | 0 |
| Strata mocy na biegun, w zależności od prądu | $P_{vid}$ | W | 0 |
| Strata mocy elementu eksploatacyjnego, w zależności od prądu | $P_{vid}$ | W | 0 |
| Strata mocy statyczna, niezależnie od prądu | $P_{vs}$ | W | 0.03 |
| Zdolność oddawania straty mocy | $P_{ve}$ | W | 0 |
| Robocza temperatura otoczenia min. | | °C | -40 |
| Robocza temperatura otoczenia maks. | | °C | 80 |
| | | | 0 |

## Dane techniczne zgodne z ETIM 6.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)

Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems (ecl@ss8.1-27-13-08-05 [ACN278008])

| | | | |
|---|---|---|---|
| System configuration | | | IT |
| Type of poles | | | Other |
| Nominal discharge surge current (8/20) | | kA | 15 |
| Nominal voltage AC | | V | 0 |
| Nominal voltage DC | | V | 1000 |
| Max. continuous voltage AC | | V | 0 |
| Max. continuous voltage DC | | V | 1170 |
| Max. PV-voltage | | V | 1170 |
| Voltage protection level | | kV | 3.7 |
| Voltage protection level L-N | | kV | 0 |
| Voltage protection level N-PE | | kV | 0 |
| Short-circuit-proof | | | No |
| Mounting method | | | DIN rail (top hat rail) 35 mm |
| Construction size | | | 2 modular spacing |
| Max. conductor cross section solid (solid, stranded) | | $mm^2$ | 35 |
| Max. conductor cross section flexible (fine-strand) | | $mm^2$ | 25 |
| With remote signalling contact | | | Yes |
| Integrated backup fuse | | | No |
| Signalling at the device | | | Optic |
| Category type 2 | | | Yes |
| Degree of protection (IP) | | | IP20 |

© 03/2018 by Eaton Industries GmbH