Build-in devices EVESYS

Rated current **16, 25 A**

Utilization category **AC-22A, AC-11**

Application

1. Application of EVESYS in house installations:
   - switching on and off of smaller loads (lighting, sockets, bells, etc.): switches
   - switching on and off of larger loads, through contactors, relays, impulse relays: switches, push-buttons
   - use in control systems (manual, switch-off, automatic): center-off changeover switch
   - display of state in installations (operation of ovens, presence of voltage, melting of fuse): signal light, switch with control light, push-button with control light
   - switching of measurement circuits (for example measurement of voltage, frequency, etc.): changeover switch
2. In industry (especially in control desks):
   - manual control and signalization of processes
   - switching on/off of auxiliary and measurement circuits (lighting, sockets, etc.)

Switch

Type	I_n [A]	Code No.	U_n [V]	number of poles	utilization category	Weight [g]	Packaging [pcs]
SG 116	16	760111107	230	1	AC-22A	62	10
SG 216	16	760121104	400	2	AC-22A	79	10
SG 316	16	760131101	400	3	AC-22A	86	10
SG 416	16	760141108	400	4	AC-22A	92	10
SG 125	25	760112108	230	1	AC-22A	62	10
SG 225	25	760122105	400	2	AC-22A	79	10
SG 325	25	760132102	400	3	AC-22A	86	10
SG 425	25	760142109	400	4	AC-22A	92	10



Switch with control light

Type	I_n [A]	Code No.	U_n [V]	number of poles	utilization category	Weight [g]	Packaging [pcs]
SLG 116	16	760211100	230	1	AC-22A	73	10
SLG 216	16	760221107	400	2	AC-22A	85	10
SLG 316	16	760231104	400	3	AC-22A	89	10
SLG 125	25	760212101	230	1	AC-22A	73	10
SLG 225	25	760222108	400	2	AC-22A	85	10
SLG 325	25	760232105	400	3	AC-22A	89	10



Technical data on page 107



Change-over switch

Type	I_n [A]	Code No.	U_n [V]	number of poles	utilization category	Weight [g]	Packaging [pcs]
ISG 116	16	760311103	230	1	AC-22A	65	10
ISG 216	16	760321100	400	2	AC-22A	79	10
ISG 125	25	760312104	230	1	AC-22A	65	10
ISG 225	25	760322101	400	2	AC-22A	79	10



Center-off change-over switch

Type	I_n [A]	Code No.	U_n [V]	number of poles	utilization category	Weight [g]	Packaging [pcs]
SSG 116	16	760611102	230	1	AC-22A	74	10
SSG 216	16	760621109	400	2	AC-22A	79	10
SSG 125	25	760612103	230	1	AC-22A	74	10
SSG 225	25	760622100	400	2	AC-22A	79	10



Push-button

Type	I_n [A]	Code No.	U_n [V]	number of poles	utilization category	Weight [g]	Packaging [pcs]
TG 216	16	764904101	230	2	AC-11	81	10



Push-button with control light

Type	I_n [A]	Code No.	U_n [V]	number of poles	utilization category	Weight [g]	Packaging [pcs]
TLG216 red	16	760412107	230	2	AC-11	86	10
TLG216 yellow	16	760413108	230	2	AC-11	86	10
TLG216 green	16	760414109	230	2	AC-11	86	10
TLG216 white	16	760411106	230	2	AC-11	86	10

Signal light LG1

Type	I_n [A]	Code No.	U_n [V]	U_{izg} [W]	number of poles	Weight [g]	Packaging [pcs]
LG1 red	2	760512100	230	1	72	10	
LG1 yellow	2	760513101	230	1	72	10	
LG1 green	2	760514102	230	1	72	10	
LG1 white	2	760511109	230	1	72	10	



Button Cap TLG

Type	Code No.	Weight [g]	Packaging [pcs]
TLG red	763712109	7	5
TLG yellow	763709109	7	5
TLG green	763708108	7	5
TLG white	763701101	7	5

This product can be used for Push button with control light and for Signal light



Modular indicators SON H

Type	Code No.	Weight [g]	Packaging [pcs]
SON H-1R	002471550	40	1/400
SON H-1G	002471551	40	1/400
SON H-3R	002471552	48	1/400
SON H-3K	002471553	48	1/400



Bell/Buzzer

Type	Code No.	U_n [V]	Weight [g]	Packaging [pcs]
Bell ZE 220	002412001	230	70	12/108
Bell ZE 8	002412002	8	70	12/108
Buzzer BE 220	002413001	230	54	12/108
Buzzer BE 8	002413002	8	54	12/108

Application
For signalling in house, command panels, etc.
Standards
CEE 15, DIN 43880



Bell transformer

Type	I_n [A]	Code No.	P_n [VA]	U_{1n} [V]	U_{2n} [V]	Weight [g]	Packaging [pcs]
Zt 8/8	1	002411005	8	230	4, 6, 8	620	1/36
Zt 8/12	0,63	002411006	8	230	6, 8, 12	600	1/36
Zt 8/8 - 2M	1	002411010	8	230	8	314	1/54
Zt 8/12 - 2M	0,63	002411011	8	230	12	312	1/54

Application
For supplying of bells, buzzers, gongs and other devices. It is protected against continual short circuits, the primary and secondary winding are separated.
Standards
IEC 61558, EN 60742

