Attractive buildings need attractive floodlights.
XLED curved

The compact and powerful sensor-switched LED floodlight for medium-sized areas.
The XLED curved is ideal for illuminating building entrances and pathways. Yet the practical floodlight does not only satisfy safety and security needs. It can also be used to create modern accent lighting. Both the sensor and the entire outdoor floodlight come in a pleasingly understated, unobtrusive look, clearly leaving centre stage to the lighting in setting off buildings and outdoor areas with masterful proficiency.

LED	10.5w						
30 years (Ø 4,5 h/day)	830 lm 79 lm/W	4000 K neutral-white	160°	max. 8 m	2 - 1000 Lux	2 sec - 70 min	






white

anthracite

Technical specifications
Dimensions: (H x W x D) 120 x 160 x 107 mm
Power supply: 230–240 V, 50 / 60 Hz
Sensor type: Passive infrared
Output: 10.5 W
Brightness: 830 lm
Efficiency: 79 lm/W
Colour temperature: 4000 K / SDCM 3
Colour rendering: Ra ≥ 85
LED life expectancy: 50,000 h (L70B10 to LM80)
LED cooling system: Active and Passive Thermo Control
Angle of coverage: 160°
Reach: max. 8 m
Floodlight adjustment range: +/- 30° swivelling
Twilight setting: 2 - 1000 lux
Time setting: 2 sec - 70 min
IP rating: IP 44
Protection class: I
Material: UV-resistant plastic with aluminium heat sink
Temperature range: -20 to +40°C

XLED curved
EAN white 4007841 012069
EAN anthracite 4007841 012052